

LIQUI MOLY



PRODUCT CATALOG NORTH AMERICA

MORE CHOICE
MORE EFFICIENCY
MORE ENTHUSIASM



FOR THE DRIVERS



We are here to support you with more than 60 local representatives in over 20 markets throughout the USA and Canada!

Not sure who your local representative is? Please visit our locator at www.liqui-moly.com or call 1-888-MOLYOIL (888-665-9645) to find out!



Additives	39
Oil Additives	6
Fuel Additives for Gasoline	7
Fuel Additives for Diesel	8
Radiator Additives	9
Truck Series	9
Workshop Pro-Line	
Service Products	10
Air-Conditioning	13
Lubricants	
Greases	14
Pastes	14
Contact Lubricants	15
Brake Fluids	15
Synthetic Motor Oils	16
Synthetic Motor Oils Low Saps (Low Ash)	17
Synthetic Motor Oils Specialties	19
Motor Oils Specialties	21
Synthetic Motor Oils Asian + American (AA)	21
Motor Oils Molygen New Generation	22
Mineral Motor Oils	24
Motor Oils Classic Cars	24
Motor Oils Heavy Duty HD	24
Gear Oils	25
ATF Gear Oils	28
Hydraulic Fluids	30
Workshop Equipment	35
Car Care	
Paint	38
Glass	38
Interior	38
Accessories	38
Cleaner	38
Service Products	39
2-Wheel/ATV/SxS/Kart/Snowmobile	
Additives	40
Motor Oils 4-Stroke Street	40
Motor Oils 4-Stroke Offroad	42
Motor Oils 2-Stroke Offroad	42
Motor Oils 4-Stroke ATV/SxS	43
Motor Oils 4-Stroke Snowmobile	43
Motor Oils 4-Stroke Snowbike	43
Gear Oils	43
Fork Oils/Shock Absorber Oils	44
Maintenance Products	44
Marine	
Additives	46
Greases	46
Motor Oils 4-Stroke	47
Motor Oils 2-Stroke	48
Gear Oils	48
Accessories	49
Gun Care Products	49
Marketing	50
Table of Contents	56



OUR RECOMMENDATIONS

For more information visit www.liqui-moly.com

Driving distance in thousand  miles **Part-No. Page** 10 20 30 40 50

 GASOLINE TREATMENT									
Pro-Line Throttle Valve Cleaning	20210	11							
Pro-Line Gasoline System Cleaning	2030	11							
 DIESEL TREATMENT									
Diesel Purge	2005	8							
Pro-Line DPF Cleaning	20110	11							
Pro-Line Diesel System Cleaning	20398	11							
Pro-Line Diesel Intake-System Cleaning	20208	11							
 AIR CONDITIONING									
A/C System Cleaning	22294	13							
 OIL CHANGE									
Pro-Line Engine Flush	2037	10							
Seal Conditioner (Oil Saver)	2020	6							
Oil Treatment (MoS ₂)	2009	6							
Engine Armor (Cera Tec)	20002	6							



60 70 80 90 100 110 120 130 140 150 160 170 180 190 200

(X)														
(X)	()	(X)												

(X)	()	()												
(X)	()	()												
(X)	()	()	(X)	()	(X)	()	()	(X)	()	()	(X)	()	()	(X)
(X)	()	()	(X)	()	()	(X)	()	()						

()	()	()	()	()	()	()	()	()	()	()	()	()	()	()

1x per year

(X)	()	()												
(X)	()	()												
()	()	()	(X)	()	()	(X)	()	()						
(X)	()	()	()	(X)	()	(X)	()	()	(X)	()	()	(X)	()	()

Additives



OIL ADDITIVES

**Cera Tec**

High-tech anti-wear additive, suitable for most 4-stroke engines as well as manual transmissions and compressors. Reduces friction and wear thanks to a unique combination of ceramic compounds and chemical anti-wear agents. It will prevent direct metal-to-metal contact and reduce friction to increase engine life and efficiency in gasoline and diesel engines.

Area of Use

Cont. Packaging Unit Part No.

300 ml 6 20002 ²⁶

**MoS₂ Anti-Friction Engine Treatment**

MoS₂ Anti-Friction Engine Treatment ensures immediate friction and wear reduction, adds an extremely protective and pressure-resistant boundary layer with low friction and lubricates during cold starts to prevent damage from lack of oil. Contributes to lower fuel consumption, longer engine life and less noise. Specifically designed for older engine designs with or without a turbocharger.

For all 4-stroke gasoline and diesel engines, with or w/o turbochargers. Compatible with most commercially available motor oils and in oil running belt. Safe for use with catalytic converters and particulate filters (GPF/DPF). One full can (300 ml) used with 3-6 Liters (3.2 to 6.4 U.S. Qts) of motor oil. Shake well before use.

300 ml 12 2009 ²⁶

**Hydraulic Lifter Additive**

Prevents and reduces hydraulic lifter noise. Cleans oil passages to remove oil flow restrictions. Restores proper hydraulic lifter function and reduces wear.

For all 4-stroke gasoline and diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF/DPF). Compatible with most commercially available motor oils and belt-in-oil systems. One full can (300 ml) used with 3-6 Liters (3.2 to 6.4 U.S. Qts) of motor oil. Not suitable for motorcycles with wet clutches.

300 ml 12 20004 ²¹
300 ml 12 20330 ²⁷

**Motor Oil Saver**

Maintains and regenerates rubber and plastic seals in the engine oil circuit of gas and diesel engines. Oil consumption due to aged and hardened valve stem seals is reduced. No more blue exhaust smoke, improved emissions. External leaks are minimized or even eliminated. Dampens engine noise and reduces repair costs. Reduces pollution and improves the environment.

Use in 4-stroke gas and diesel engines, with or without turbochargers. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF). Not suitable for use with wet clutches! One full can (300 ml) used with 3-5 Liters (3.2 to 5.3 U.S. Qts) of motor oil. The product can be added at any time, sealing first takes effect after about 600-800 km (400-500 miles).

300 ml 12 2020 ²¹
300 ml 12 20320 ²⁷

**Viscoplus for Oil**

Mono functional additive that stabilizes motor oil viscosity. Provides outstanding protection against mechanical and permanent shear losses in extreme conditions and prevents viscosity loss caused by frequent cold starts.

For all 4-stroke gasoline and diesel engines, with or without turbochargers. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF). One full can (300 ml) used with 3-5 Liters (3.2 to 5.3 U.S. Qts) of motor oil. Not suitable for motorcycles with wet clutches.

300 ml 12 20206 ²¹
300 ml 12 20338 ²⁷

OIL ADDITIVES



ATF Additive

Keeps rubber and plastic seals in automatic transmissions soft and pliable. Leaks caused by hardened and brittle seals are prevented or eliminated. Cleans internal oil passages to allow proper oil flow while restoring the oil's performance. Reduces noise and improves shift performance in automatic transmissions. Extends usable transmission life.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. Packaging Unit Part No.

250 ml 6 20040 ²⁶



MoS₂ Antifriction for Gears

Stabilized solid lubricant concentrate suspended in mineral oil. Thanks to its high MoS₂ content and special additives, it is suitable for all manual motor vehicle transmissions and differentials without limited slip function.

For all automatic transmissions that are filled with Dexron II and Dexron III based fluids. One full tube (250 ml) used with 4-8 Liters (4.2 to 8.5 U.S. Qts) of ATF fluid.

50 g 12 2019 ²¹
50 g 12 22084 ²⁷



Power Steering Oil Leak Stop

Keeps rubber and plastic seals in hydraulic power steering systems soft and pliable. Leaks caused by hardened and brittle seals are prevented or eliminated. Cleans internal oil passages to allow proper oil flow, reduces noise levels and extends service life while reducing repair costs.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For all manual transmissions, axle drives, differential transmissions and mechanical steering systems. Miscible with most commercially available gear oils. Not suitable for automatic transmissions and other wet clutch systems. One full tube (50 g) used with 1-2.5 Liters (1 to 2.7 U.S. Qts) of gear oil.

35 ml 12 20284 ²⁶

FUEL ADDITIVES FOR GASOLINE



Speed Tec Gasoline

High-tech fuel additive, developed specifically for improved throttle response under partial engine load. Optimizes fuel atomization and combustion, cleans fuel system while providing maximum engine performance and efficiency.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for steering gears that are filled with Dexron II, Dexron III, Dexron VI or central hydraulic system oils. Add to the compensating reservoir of the steering system. One full tube (35 ml) used with up to 1 liter (1.1 U.S. Qts) of steering fluid.

250 ml 6 20234 ²¹
250 ml 6 20340 ²⁷



Valve Clean

A combination of active agents, specifically developed to clean and maintain intake valves and the combustion chamber of port- and multi-port fuel injected engines. Restores engine efficiency and protects against corrosion in the fuel system.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use in all 4- and 2-stroke gasoline engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF). Contents (250 ml) is sufficient for 25-75 Liters (7 gal. to 20 gal.) fuel. For consistent use when refueling.

150 ml 12 2001 ²¹
150 ml 12 7701 ²⁷



Jectron Fuel Injection Cleaner

A combination of additives to clean and maintain the fuel system of port injected and carbureted gasoline engines. Cleans injectors, the combustion chamber and protects against corrosion. Restores proper fuel atomization and improves engine efficiency. Regular use keeps the fuel system in perfect working order.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use in all 4-stroke gasoline engines with port- and multi-port fuel injection, with or w/o turbochargers. Safe for use with catalytic converters and particulate filters (GPF). One full can (150 ml) used with 25-75 Liters (7 gal. to 20 gal.) of fuel.

300 ml 12 2007 ²¹
300 ml 12 7711 ²⁷

Additives



FUEL ADDITIVES FOR GASOLINE



DIjectron

The unique combination of proven PEA technology and the latest additive generation achieves maximum cleaning performance in the combustion chamber, **in and around** the injector tip and in the entire fuel system. Furthermore, DIjectron stops the formation of new deposits so that complex injector systems always work at the highest efficiency. Regular use of DIjectron significantly reduces the risk of engine damage caused by Low Speed Pre Ignition (LSPi), optimizes exhaust gas emissions and protects the fuel system from corrosion.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. Packaging Unit Part No.

300 ml 12 **22076** ²¹
300 ml 12 **22110** ²⁷

LIQUI MOLY recommends DIjectron particularly for modern 4-stroke gasoline direct injection (GDI) engines. Contents (300 ml) is sufficient for 40-70 Liters (10.5 gal. to 18 gal.) of fuel.



Hybrid Additive

A combination of agents, developed specifically for late model hybrid engines. Removes deposits in the fuel system and protects against corrosion. Stabilizes the fuel and protects against aging and oxidation. Diminished fuel degradation allows better engine performance and efficiency.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use in all 4-stroke gasoline engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF). To be added directly into the fuel tank. Contents (250 ml) is sufficient for 25-75 Liters (7 gal. to 20 gal.) gasoline (dose 1:300).

250 ml 6 **20288** ²¹
250 ml 6 **20342** ²⁷

FUEL ADDITIVES FOR DIESEL



Super Diesel Additive

A combination of additives to clean and maintain the diesel fuel system. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel. For best results add Super Diesel Additive every 2,000 km (1,200 miles) to fuel. Contents (300 ml) is sufficient for 25-75 Liters (7 gal. to 20 gal.) fuel.

300 ml 12 **2002** ²¹
300 ml 12 **7702** ²⁷



Diesel Particulate Filter Protector

Reduces formation of soot during combustion in the engine. Improves engine performance and emissions control. Reduces clogging of the DPF caused by soot as a combustion product.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Added to diesel fuel for all diesel engines with DPF, particularly in modern high pressure engines in passenger and commercial motor vehicles, tractors, construction machinery and stationary engines. Ideally suitable for short distance or short time operation. Suitable for use with HVO / XTL Diesel fuel. Contents (250 ml) is sufficient for 50-75 Liters (13 gal. to 20 gal.) fuel.

250 ml 6 **2000** ²¹



Diesel Purge

Developed for cleaning fuel systems and injectors within minutes and restore lost power caused by deposits. Ideally Diesel Purge is added into the fuel filter housing. It will eliminate knocking, pinging and exhaust smoke. Improves start up performance.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel.

500 ml 12 **2005** ²¹
500 ml 12 **7704** ²⁷

Preventive use: Fill the fuel filter up with Diesel Purge when doing filter replacement, put the rest in tank. In case of problems run the engine directly with Diesel Purge through fuel line or diesel filter.

Additives

RADIATOR ADDITIVES



Radiator Cleaner

Removes deposits in cooling systems of all water cooled engines. It removes scale, grease, sludge and other deposits to allow restored performance and proper cooling performance.



Radiator Stop Leak

Will immediately seal small leaks caused by external damage, porous solder joints and hairline cracks in cooling systems of all water cooled engines. Coolant is prevented from entering the combustion chamber due to internal leaks from head gasket etc. It does not react with oxygen or heat and will never prevent system flow or cause overheating. Radiator Stop Leak works as long as it's in the coolant.

TRUCK SERIES



Truck Series Oil Treatment

Ensures immediate friction and wear reduction, adds an extremely protective and pressure-resistant boundary layer with low friction and lubricates during cold starts to prevent damage from lack of oil. Contributes to lower fuel consumption, longer engine life and less noise. Specially designed for older engine designs with or without a turbocharger. Regular use keeps the engine in perfect working order.



Truck Series Complete Gasoline System Cleaner

An effective mixture of additives to clean and maintain the fuel system of port injected and carbureted gasoline engines. Cleans injectors, the combustion chamber and protects against corrosion. Restores proper fuel atomization and improves engine efficiency. Regular use keeps the fuel system in perfect working order.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Truck Series Complete Diesel System Cleaner

An effective mixture of additives for rapid removal of performance diminishing deposits from the fuel system in all kinds of diesel engines. Cleans injectors, the combustion chamber and restores proper fuel atomization for improved engine efficiency.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer, and n-hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Truck Series Diesel Performance and Protectant

An effective mixture of additives that clean and maintain diesel fuel systems. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Truck Series DPF Protector

An effective mixture of additives that reduce soot formation during combustion while improving engine performance and reducing emissions. Reduces premature clogging of the DPF by soot and extends the DPF regeneration intervals.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use	Cont.	Packaging Unit	Part No.
Suitable for all coolant and heating systems (exception: Low Conductivity-coolants). Does not contain aggressive acids or alkalis and is acid neutralising. Contents (300 ml) is sufficient for 4-10 Liters (1 gal. to 2.6 gal.) coolant water.	300 ml	12	2051 ²¹
	300 ml	12	20336 ²⁷

For any water based cooling system with or without filters (exception: Low Conductivity-coolants). Safe to use with aluminum and plastic radiators. Contents (250 ml) is sufficient for 10 Liters (2.6 gal.) coolant. Compatible with most types of coolant or anti-freeze. May be used as a preventive.	250 ml	12	20132 ²¹
	250 ml	12	20332 ²⁷

For all 4-stroke gasoline and diesel engines, with or without turbochargers. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF / DPF). One full can (500 ml) used with 5-10 liters (5.3 to 10.6 U.S. Qts) of motor oil.	500 ml	6	20256 ²⁶
---	--------	---	---------------------

Suitable for use in all 4-stroke gasoline engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF). One full can (500 ml) used with 30 – 115 liters (8 gal. to 30 gal.) of fuel. For a lasting effect we recommend to use at least every 2,000 km (1,200 miles).	500 ml	6	20250 ²¹
--	--------	---	---------------------

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel. One full can (500 ml) used with 30 – 115 liters (8 gal. to 30 gal.) of fuel.	500 ml	6	20252 ²¹
--	--------	---	---------------------

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel. One full can (500 ml) used with 30 – 150 liters (8 gal. to 40 gal.) of fuel. For a lasting effect we recommend to use at least every 2,000 km (1,200 miles).	500 ml	6	20254 ²¹
--	--------	---	---------------------

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel. Contents (500 ml) is sufficient for 50-115 Liters (14 gal. to 30 gal.) diesel.	500 ml	6	20258 ²¹
--	--------	---	---------------------

SERVICE PRODUCTS



Pro-Line Turbocharger Additive

Provides initial lubrication of new or replaced turbochargers to prevent damage due to oil starvation. Damage to turbocharger may occur within seconds of engine start if not lubricated properly. Pro-Line Turbocharger additive will provide needed protection and allow proper break-in of new units which prevents additional repairs.

Area of Use

Cont. Packaging Unit Part No.

20 g 12 **22074** ²¹



Pro-Line Engine Flush

A highly effective formulation designed for quick and safe removal of deposits in engines before an oil change. Optimizes oil consumption, guarantees proper oil pressure in hydraulically activated systems and ensures proper oil flow after a cold start. Allows the fresh oil to immediately develop full performance while restoring full engine performance and reducing exhaust emissions.

WARNING: This product can expose you to chemicals including 2-ethylhexyl acrylate, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For all 4-stroke gasoline and diesel engines. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF).

500 ml 6 **2037** ²¹
500 ml 6 **7712** ²⁷
5 l 3 **22246** ²¹



Pro-Line Engine Protection

Highly effective additive formulated with concentrated MoS₂. Ensures immediate friction and wear reduction, adds an extremely protective and pressure-resistant boundary layer with low friction and protects during cold starts as well as under extreme operation conditions to prevent damage from lack of oil. Contributes to lower fuel consumption, longer engine life and less wear. Specifically designed for engines with large oil volumes and heavy load.

For all 4-stroke gasoline and diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF/DPF). Compatible with most commercially available motor oils and in oil running belt. One full can (500 ml) used with 3-5 Liters (3.2 to 5.3 U.S. Qts) of motor oil. 5 l used with 30-50 Liters (32 to 53 U.S. Qts) of motor oil.

1 l 6 **22247** ²¹



Pro-Line Motor Oil Saver

Maintains and regenerates rubber and plastic seals in the engine oil circuit of gas and diesel engines. Oil consumption due to aged and hardened valve stem seals is reduced. Reduces exhaust smoke and emissions. External leaks are minimized or even eliminated. Dampens engine noise and lowers repair costs. Reduces pollution and improves the environment.

Use in all 4-stroke gas and diesel engines, with or without turbochargers. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF). One full can (1 l) used with 30-50 liters (32 - 53 U.S. Qts) of motor oil.

1 l 6 **22250** ²¹



Pro-Line Automatic Transmission Cleaner

A highly effective formulation developed for safe internal cleaning of automatic transmissions during maintenance service. Eliminates problems and restores proper shifting performance in automatic transmissions. Allows the fresh oil to immediately develop full performance. Maintains operating efficiency, smooth shifting and overall behavior while maximizing longevity.

Use in 4-stroke gas and diesel engines, with or without turbochargers. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF). One full can (1 l) used with 10-15 Liters (10.5 to 16 U.S. Qts) of motor oil.

1 l 6 **20224** ²⁶



Pro-Line ATF Additiv

Modern additive to keep rubber and plastic seals in automatic transmissions soft and pliable. Leaks caused by hardened and brittle seals are prevented or eliminated. Regular preventive use with every oil change extends the service life of the transmission seals.

WARNING: This product can expose you to chemicals including sulfur dioxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Regular preventive use with every oil change prevents or eliminates leaks caused by hardened and brittle seals. Can be used with all common ATF oils.

250 ml 6 **22302** ²⁶

SERVICE PRODUCTS



Pro-Line Gasoline System Cleaner

An effective mixture of additives used to clean and maintain fuel systems of injected or carbureted gasoline engines. Cleans injectors and the combustion chamber, restores proper fuel atomization and improves engine efficiency. Suitable for use as problem solver and for preventive maintenance.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Pro-Line Diesel System Cleaner

A highly effective mixture of additives with strong cleaning power for rapid removal of deposits from the fuel system in all kinds of diesel engines. Cleans injectors and the combustion chamber. Restores engine efficiency and improves emission values. Suitable for use as a problem solver and for preventive maintenance.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Pro-Line Diesel Particulate Filter Purge

A highly effective fluid used for cleaning soot clogged DPF units without disassembly. Dissolves contaminants inside DPF units, restores vehicle performance and fuel consumption. Regular use help prevent expensive repairs. Always use in combination with Pro-Line Diesel Particulate Filter Cleaner (part no. 20110). To apply use DPF Pressurized Tank Spray Gun (part no. 7946), DPF-Probe with 5 interchangeable tips (part no. 7945) and if needed DPF Spray Probe long (part no. 20630).



Pro-Line Diesel Particulate Filter Cleaner



A highly effective fluid used for cleaning soot clogged DPF units without disassembly. Dissolves contaminants inside DPF units, restores vehicle performance and fuel consumption. Regular use help prevent expensive repairs. Always use in combination with Pro-Line Diesel Particulate Filter Purge (part no. 20112). To apply use DPF Pressurized Tank Spray Gun (part no. 7946), DPF-Probe with 5 interchangeable tips (part no. 7945) and if needed DPF Spray Probe long (part no. 20630).

WARNING: This product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Pro-Line Throttle Valve Cleaner



A blend of highly effective cleaning agents designed to clean throttle bodies of 4-stroke gasoline engines. It is also ideal for maintaining modern GDI engine intake manifolds and intake valves. Dissolves and removes deposits and ensures proper function of moving parts. Regular use restores efficiency and minimizes operating costs. Recommended for preventive use every 10,000 miles/15,000 km/12 months.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Pro-Line Diesel Intake System Cleaner



A blend of highly effective cleaning agents designed to clean and maintain diesel intake manifolds and intake valves. Dissolves and removes deposits and ensures proper function of moving parts. Regular use restores efficiency and minimizes operating costs. Recommended for preventive use every 10,000 miles/15,000 km/12 months.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Pro-Line Injector and Glow Plug Dismantling Aid

Special purpose high-performance fluid to aid in removing stuck injectors, glow and spark plugs. Removes heavy dirt, debris, deposits and gummed up sediments with ease and allows easy component removal.

WARNING: This product can expose you to chemicals including ethylbenzene, which is known to the State of California to cause cancer and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Area of Use	Cont.	Packaging Unit	Part No.
Suitable for use in all 4-stroke gasoline engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF). One full Can (500 ml) used with 30 - 70 liters (8 gal. to 18 gal.) of fuel.	500 ml	6	2030 ²¹
	500 ml	6	7986 ²⁷

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel. One full Can (500 ml) used with 30 to 80 liters (8 to 21 gallons) of fuel. Preventive application: Add to the fuel at every inspection. Problem solver: Add to fuel to cure acute engine problems.	500 ml	6	2032 ²¹
	500 ml	6	20398 ²⁷

For cleaning of diesel particle filter (DPF) as installed on vehicle.	500 ml	6	20112 ²⁶
For professional repair shop use only.			

For cleaning of diesel particle filter (DPF) as installed on vehicle.	1 l	6	20110 ²¹
	1 l	6	20322 ²⁷

Suitable for gasoline direct-injected, port- or multi-port injected 4-stroke gasoline engines, with or w/o turbochargers, catalytic converters and particulate filters (GPF).	400 ml	6	20210 ²¹
---	--------	---	---------------------

Suitable for use in all 4-stroke diesel engines, with or w/o turbochargers, diesel direct-injection, EGR (exhaust gas recirculation) valve, catalytic converters and particulate filters (DPF).	400 ml	6	20208 ²¹
---	--------	---	---------------------

Used for removal of injectors, spark and glow plugs etc.	400 ml	6	22242 ²¹
--	--------	---	---------------------

SERVICE PRODUCTS



Pro-Line Injector and Glow Plug Grease

Part synthetic and metal-free specialty grease designed specifically to lubricate injectors, spark and glow plugs as installed. When used properly, this specialty grease creates a moisture barrier which protects the outside of injector and glow plugs from corroding and to assist in removal when repair is needed.

Area of Use

Cont. Packaging Unit Part No.

20 g 12 22243 ²¹




DPF Pressurized Tank Spray Gun

The Spray-Gun is powder coated for protection and equipped with a non-return pressure valve. It comes supplied with a European style hose coupling. Reservoir size is 1 liter (34 FL OZ). The built-in manual flow valve allows precise control of spray volume. The Liqui Moly spray gun design provides a finely atomized spray pattern for a more efficient DPF cleaning.

Used for lubrication of any high-load sliding surface and to allow separation of components subjected to extended heat stress such as injectors, spark and glow plugs, pins and fasteners. Only apply to clean and moisture free components. Apply a thin and even coat using finger, brush or lint-free cloth. Use the appropriate amount to achieve necessary coating thickness for proper protection.

1 Piece 1 7946 ²⁶



DPF-Probe With 5 Interchangeable Tips

Specially developed probe with 5 different adjustable and articulating tips made from stainless steel for application of Pro-Line Diesel Particulate Filter Cleaner and Pro-Line Diesel Particulate Filter Purge. The probe has a flexible hose connection with a length of 1 m (39,4") that fits the DPF Pressurized Tank Spray Gun (part no. 7946).

Designed for use together with Liqui Moly DPF-Probe (LM7945) and when applying Pro-Line Diesel Particulate Filter Cleaner and Pro-Line Diesel Particulate Filter Purge. Operating air pressure is 6-8 bar (90 - 120 psi).

1 Piece 1 7945 ²⁶



DPF Spray Probe, Long (30 cm)

Straight probe (length 30 cm/12") offered as an added accessory to the DPF-Probe w. 5 interchangeable tips (part no. 7946) for use with several VW/Audi and vehicles with larger diameter particle filter units.

Depending on the type of vehicle, enables ideal access for cleaning passenger car diesel particulate filters (DPF/FAP) when installed.

1 Piece 1 20630 ²⁶



DPF/GPF Cleaner

A mixture of highly efficient, non-flammable cleaning agents formulated to burn soot more efficiently inside gasoline and diesel engines' exhaust particulate filter units (GPF/DPF). Use to maintain the proper function of particulate filters without removal from the vehicle. Used as a preventative measure every 10,000 miles (15,000 km) or 12 months

⚠ WARNING: This product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Enables DPF cleaning of large diameter particle filters on trucks, buses etc., as well as for numerous vehicles of the Volkswagen Group based on the MQB platform.

400 ml 12 22223 ²¹



Pro-Line Diesel System Cleaner Concentrate

A highly effective mixture of additives for rapid removal of performance diminishing deposits from the fuel system in all kinds of diesel engines. Cleans injectors, the combustion chamber and restores proper fuel atomization for improved engine efficiency and lowest emission values.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer, and n-hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use for regular maintenance of particulate filters (PF) installed on the vehicle. This product is not intended for DIY projects and is strictly for use by professional repair shops.

1 l 6 22248 ²¹



Pro-Line Super Diesel Additive

An effective blend of additives to clean and maintain all common diesel fuel systems. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine efficiency and lowest emissions. Regular use keeps the fuel system in perfect working order and minimizes operating costs.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel. Dosage is 1:300, so 1 Liter is sufficient for 300 Liters (80 gal.) of fuel.

1 l 6 22249 ²¹

SERVICE PRODUCTS



Pro-Line Super Diesel Additive K

A concentrated blend of additives to clean and maintain all common diesel fuel systems. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine efficiency and lowest emissions. Regular use keeps the fuel system in perfect working order and minimizes operating costs.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. Packaging Unit Part No.

20 l 1 22245 ²¹

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel. Dosage is up to 1:500, so 1 Liter is sufficient for up to 500 Liters (132 gal.) of fuel.

AIR-CONDITIONING



Air-Conditioner System Cleaner Gun

A special tool for the application of the LIQUI MOLY A/C System Cleaning Fluid (part no. 22294). Produces a circular spray pattern to allow proper cleaning of evaporator. The reservoir uses a quick connector for easy hook-up and handling during application.

Developed specially for cleaning common air conditioning systems in cars, commercial vehicles, buses, RVs, etc. with LIQUI MOLY A/C System Cleaner (part no. 22294).

1 Piece 1 4090 ²⁶



Air-Conditioning System Gun Probe

Long, flexible spray probe for simple access to the evaporator and with a 360° nozzle for clean distribution of the cleaning fluid.

Cleaning automotive and industrial air conditioners.

1 Piece 1 4099 ²⁶



A/C System Cleaner

A ready-to-use fluid that effectively cleans air conditioning systems in cars, commercial vehicles, buses, RVs, etc. It eliminates the causes of unpleasant odors from the evaporator and air ducts and leaving a fresh scent. For professional use only.

Suitable for cleaning common air conditioning systems in cars, commercial vehicles, buses, RVs, etc.

1 l 6 22294 ²⁶

Lubricants



GREASES

**Battery Clamp Grease**

Protects battery terminals and electrical contacts from corrosion and oxidation. It is compatible with most plastics, ensures safe starting, bright light and longer battery life. Prevents acid damage, leakage current and contact resistance. Certification: DIN 51502 K2G-30. Service temperature: -30 °C to +100 °C (-22 °F to +212 °F).

Area of Use

Cont. 50 g 12 Packaging Unit 20244 Part No. 21

Use on battery terminals and connectors along with terminal connectors in vehicle electronics.

**Multipurpose Grease**

High performance Multipurpose Grease for use in a wide range of applications in motor vehicles and general machine lubrication. Carefully selected ingredients offer good corrosion protection, ensures long-term lubrication in damp and dusty environments. Resists cold and hot water washout. Certification: DIN 51502 K2K-20 Service temperature: -25 °C to +120 °C (-13 °F to +248 °F). Intermittent up to +130 °C (+266 °F).

Suitable for a wide application range in all motor vehicles and for general machine lubrication.

400 g 12 20246 26

**LM 50 Litho HT**

High performance grease used in a wide range of applications in motor vehicles. Specifically recommended for fast spinning bearings with high load such as wheel bearings. Provides excellent wear protection and high-pressure absorbance capacity. Certification: DIN 51502 KP2N-30. Service temperature: -30 °C to +140 °C (-22 °F to +284 °F). Intermittent up to +180 °C (+356 °F).

Suitable for a wide application range in all motor vehicles, specifically suitable for fast spinning bearings with high load such as wheel bearings.

400 g 12 20248 26

**Long-Life Grease + MoS2**

A high-performance grease suitable for a wide range of applications in all motor vehicles and for general machine lubrication. Thanks to added MoS₂ it provides excellent protection during extreme loads and high heat while providing excellent dry-run properties. Designed as a CV-joint lubricant it's also recommended for high-load bearings and joints, splined shafts, threads, guides, and constant velocity drive joints. The added MoS₂ gives the grease its grey color.

Suitable for a wide application range in all motor vehicles and for general machine lubrication. Not suitable for high speed bearings such as wheel bearings.

100 g 12 2003 26
400 g 12 22255 26

WARNING: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

PASTES

**Brake Anti-Squeal Paste**

A synthetic based specialty with a solid agent to prevent and eliminate noise from brake pads. It is extremely adhesive and high temperature resistant, it resists road salt and water wash-out. With excellent corrosion protection and particularly suited for use with aluminum and magnesium materials as well as on vehicles with ABS/ESP systems. Application range -40 °C to +1200 °C (-104 °F to +2.192 °F).

Suitable for use in most common disk brake systems. Must never be applied to the friction surface of the brake disc / brake pads.

200 ml 6 20240 21
250 g 6 22092 21

**Ceramic Paste**

A modern, multifunctional formulation that can be used in a variety of applications. Thanks to its high adhesion and high temperature resistance it can be used as a release agent, to prevent seizing, cold welding, rust freezing and stick-slip. Metal-free and non-conductive. Suitable for use with aluminum and magnesium materials. Application range -40 °C to +1.400 °C (-104 °F to +2.552 °F).

Use when high temp and/or anti-seize lubrication is needed or general lubrication of threaded fasteners.

200 ml 6 20242 21
250 g 6 22094 26

LM 48 Installation Paste

Is used for assembly of engines, gearboxes, industrial machinery or for press fitting etc. Very adherent on polished surfaces. Use on engine bearings, piston skirts, camshaft lobes etc. Prevents dry-run damage at start-up. Allows easy assembly of tight-fitting parts. Provides protection from scoring during press fit. Uses a synergistically active and unique solid lubricant system of zinc sulfide, graphite, fluorides and tungsten disulfide. Service temperature: -35 °C to +450 °C (-31 °F to +842 °F).

Suitable for assembly of engines, gearboxes (dry clutch only), industrial machinery, when press fitting etc.

50 g 12 20216 26
1 kg 4 22040 26



Lubricants

PASTES



LM 508 Anti-Seize Compound

A release agent, specifically designed for high temperature applications on threaded connections and parting surfaces which are exposed to high temperatures, high pressures and corrosive effects in turbines, compressor equipment, exhaust systems, spark plug threads etc. Operating temperature range: -35 °C to +1100 °C (-31 °F to +2012 °F).

⚠ WARNING: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. 100 g 12 Part No. 2012 ²⁶

For high temperature applications on threaded connections and parting surfaces which are exposed to high temperatures, high pressures and corrosive effects in turbines, compressor equipment, exhaust systems, spark plug threads etc.



Brake Pin Lube

Special purpose brake caliper slide and pivot point lubricant for use during assembly and repair of brake calipers. Provides proper slide pin and pivot point movement for equalized brake pad wear and accurate function. Reduces brake noise thanks to vibration damping properties. Compatible with most rubber and plastics. Prevents dirt, debris and water intrusion for maximum corrosion protection and service life. Corresponds to OEM requirements for caliper pin greases.

⚠ WARNING: This product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use to lubricate brake caliper slides, pivot points and caliper O-rings. Minute amounts in contact will not affect DOT 3, DOT 4 (LV/SL6) and 5.1 brake fluids. Clean and dry area to be treated. Apply with brush, clean cloth or sponge. Remove excess.

5 g 50 Part No. 22237 ²⁶

CONTACT LUBRICANTS



Electronic Spray

Fully synthetic, silicone free contact spray, formulated for use on vehicle electronic and general electrical systems. Reduces fretting and corrosion, suppresses moisture. It is neutral to paints, common plastics and rubber. Cleans and protects electrical connectors.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use on vehicle electronic and general electrical systems.

200 ml 6 Part No. 20298 ²¹

BRAKE FLUIDS



Brake Fluid DOT 4

Synthetic formulation based on glycol ethers, alkyl polyglycols and glycol ether esters. A high wet and dry boiling point and unique inhibitors provide corrosion and oxidation protection at high temperatures which guarantees full function even during extreme conditions. Special scavengers are used to suppress steam at increased moisture levels.

Specifications and approvals: FMVSS 116 DOT 3, FMVSS 116 DOT 4, ISO 4925 Class 3, ISO 4925 Class 4, SAE J 1703, SAE J 1704

For hydraulic systems that specify a fluid consistent with current product specifications. Observe the manufacturers instructions!

250 ml 24 Part No. 20152 ²¹
500 ml 24 Part No. 20154 ²¹
1 l 6 Part No. 22078 ²¹



Brake Fluid DOT 5.1

Synthetic formulation based on glycol ethers, alkyl polyglycols and glycol ether esters which guarantees full function even during extreme conditions. A higher wet and dry boiling point compared to DOT 3 and DOT 4 brake fluids and unique inhibitors provide corrosion and oxidation protection at high temperatures. Special scavengers are used to suppress steam at increased moisture levels.

Specifications and approvals: FMVSS 116 DOT 3, FMVSS 116 DOT 4, FMVSS 116 DOT 5.1, ISO 4925 Class 3, ISO 4925 Class 4, ISO 4925 Class 5.1, SAE J 1703, SAE J 1704

For hydraulic systems that specify a fluid consistent with current product specifications. Observe the manufacturers instructions!

250 ml 24 Part No. 20158 ²¹
500 ml 24 Part No. 22286 ²¹
1 l 6 Part No. 22287 ²¹



Brake Fluid SL6 DOT 4

Low viscosity brake fluid specifically formulated for quickest response and outstanding performance in modern vehicles with electronic safety systems such as ESP / ABS / TC systems. High wet and dry boiling points combined with unique inhibitors for excellent performance and optimum corrosion protection in all conditions. Synthetic formulation uses a base of glycol ethers, alkyl polyglycols and polyglycol esters which provide ultimate brake system lubrication and protection.

Specifications and approvals: FMVSS 116 DOT 3, FMVSS 116 DOT 4, ISO 4925 Class 6, SAE J 1703, SAE J 1704

For use in all hydraulic brake and clutch systems that specify a fluid consistent with current product specifications. Particularly suited for use in modern vehicles with ESP / ABS / TC systems.

250 ml 6 Part No. 22232 ²¹
500 ml 24 Part No. 22288 ²¹
1 l 6 Part No. 22238 ²¹

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants



BRAKE FLUIDS

**Brake Fluid 4 in 1**

A High-performance, multi-purpose brake fluid based on glycol ethers. The state-of-the-art formulation has been specifically developed to maximize the lifetime of components in hydraulic brake and clutch systems of vehicles that require brake fluids such as DOT 4, SL6 DOT 4 (DOT 4 LV), DOT 5.1 and ISO Class 7. The formulation has excellent material compatibility, a low viscosity and electrical conductivity, and excellent wet and dry boiling points. Additionally, it minimizes wear on sensitive brake components. Perfect for use in most vehicles, including electric and hybrid models. Excellent for use in all standard and modern, electronically controlled hydraulic systems, including ESP/ABS/TC systems, that require a fluid with current product specifications.

Specifications and approvals: FMVSS 116 DOT 4, FMVSS 116 DOT 4 LV, FMVSS 116 DOT 5.1, FMVSS 116 DOT 5.1 LV, ISO 4925 Class 4, ISO 4925 Class 5.1, ISO 4925 Class 6, ISO 4925 Class 7, SAE J 1704

Area of Use

Cont. Packaging Unit Part No.

5 l 4 **22295** ²¹

For hydraulic brake and clutch systems that require current product specifications. Ideal for electronically controlled systems such as ESP/ABS/TC and electric and hybrid vehicles. Not for use in classic cars that call for DOT 3 fluids or applications where DOT 5 (silicone-based) fluids are required or recommended!

SYNTHETIC MOTOR OILS

**Synthoil Energy A40 SAE 0W-40**

Modern, fully synthetic top-of-the-line motor oil. Provides quick oil delivery throughout the engine during cold-start and optimum lubrication with maximum protection under all operating conditions. Beneficial for increased engine life in high tech engines. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA A3, ACEA B4, API SP, Porsche A40

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW Longlife-01 (up to 2018)*, Ford WSS-M2C 937-A, MB 229.3, MB 229.5, VW 502 00, VW 505 00

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l 6 **2049** ²⁶
5 l 4 **2050** ²⁶
205 l 1 **22058** ²⁶

**Special Tec LL SAE 5W-30**

Modern, fully synthetic all-season motor oil for superior performance and long engine life. For gasoline and diesel vehicles without particulate filters (GPF/DPF). Exceeds strict test requirements demanded by major manufacturers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA A3, ACEA B4, API SL, MB-Approval 229.5, VW 502 00, VW 505 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW Longlife-01, Opel GM-LL-A-025, Opel GM-LL-B-025

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l 6 **2248** ²⁶
5 l 4 **2249** ²⁶
20 l 1 **20124** ²⁶
60 l 1 **20364** ²⁶
205 l 1 **20365** ²⁶
1000 l 1 **20733** ²⁶

**Leichtlauf High Tech SAE 5W-40**

Top class fully synthetic, all-season motor oil for superior performance and long engine life. For gasoline and diesel vehicles without particulate filters (GPF/DPF). Exceeds strict test requirements specified by major manufacturers. Safe with catalytic converters and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA A3, ACEA B4, API SP, BMW Longlife-01, MB-Approval 229.5, Peugeot Citroen (PSA) B71 2296, Porsche A40, Renault RN 0700, Renault RN 0710, VW 502 00, VW 505 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler MS-10725, Chrysler MS-10850, Fiat 9.55535-H2, Fiat 9.55535-M2, Fiat 9.55535-N2, Fiat 9.55535-Z2, GWM, HAVAL, Opel GM-LL-B-025, Peugeot Citroen (PSA) B71 2294

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l 6 **2331** ²⁶
1 l 1 **22276** ²⁶
5 l 4 **2332** ²⁶
20 l 1 **20122** ²⁶
60 l 1 **20362** ²⁶
205 l 1 **20363** ²⁶
1000 l 1 **20731** ²⁶

**Synthoil Premium SAE 5W-40**

Low-friction, fully synthetic motor oil for all-season use in gasoline and diesel engines without particulate filters (GPF/DPF). Observe manufacturers instructions.

Specifications and approvals: ACEA A3, ACEA B4, API SN PLUS, API CF

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW Longlife-98, MB 229.3, Opel GM-LL-A-025, Opel GM-LL-B-025, Renault RN 0700, Renault RN 0710, VW 502 00, VW 505 00

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l 12 **2040** ²⁶
5 l 4 **2041** ²⁶
60 l 1 **2099** ²⁶
205 l 1 **2069** ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

SYNTHETIC MOTOR OILS



Synthoil Race Tech GT1 SAE 10W-60

Fully synthetic motor oil designed for extreme conditions. Developed specifically for high output, high performance engines. The wide viscosity range and unique formulation provides outstanding thermal stability for proper lubrication and low engine wear in tough conditions.

Specifications and approvals: ACEA A3, ACEA B4, API SN

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Fiat 9.55535-H3

Area of Use

Cont.	Packaging Unit	Part No.
1 l	6	2068 ²⁶
5 l	4	2024 ²⁶
20 l	1	20127 ²⁶
60 l	1	20374 ²⁶
205 l	1	20375 ²⁶

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

SYNTHETIC MOTOR OILS LOW SAPS (LOW ASH)



Top Tec 6200 SAE 0W-20

Fully synthetic superior low friction motor oil. Specifically developed for the high requirements of select Volkswagen and Audi vehicles. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. The innovative additive technology ensures excellent protection against wear, superb engine cleanliness and greater oxidation stability. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C5, Ford WSS-M2C 956-A1, Porsche C20, VW 508 00, VW 509 00

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions! **Not backwards compatible.**

1 l	6	20236 ²⁶
5 l	4	20238 ²⁶
20 l	1	22186 ²⁶
60 l	1	22235 ²⁶
205 l	1	22089 ²⁶
1000 l	1	22164 ²⁶



Top Tec 6600 SAE 0W-20

Fully synthetic superior low friction motor oil. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. The innovative additive technology ensures excellent protection against wear, superb engine cleanliness and greater oxidation stability. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C5, C6, API SQ, BMW Longlife-17 FE+, ILSAC GF-7A, Jaguar / Land Rover STJLR.03.5006, MB-Approval 229.71, MB-Approval 229.72, Opel OV 040 1547 - A20

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler MS-12145, Fiat 9.55535-GSX, Ford WSS-M2C 947-B1, Ford WSS-M2C 954-A1, Ford WSS-M2C 962-A1

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	22044 ²⁶
5 l	4	22046 ²⁶
20 l	1	22048 ²⁶
205 l	1	22049 ²⁶
1000 l	1	22140 ²⁶



Top Tec 6610 SAE 0W-20

Fully synthetic superior low friction motor oil. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. The innovative additive technology ensures excellent protection against wear, superb engine cleanliness and greater oxidation stability. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C5, API SP, Ford WSS-M2C 952-A1, Jaguar / Land Rover STJLR.03.5006, MB-Approval 229.71, Opel OV 040 1547 - A20

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: GM dexos D

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

5 l	4	22190 ²⁶
205 l	1	22193 ²⁶



Top Tec 4210 SAE 0W-30

Top class fully synthetic, low-SAPS motor oil for superior performance and best engine efficiency. Designed for use in numerous Volkswagen and Audi vehicles and also suitable for use in a variety of BMW diesel, Mercedes-Benz as well as specific Porsche models, etc. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C3, BMW Longlife-04, MB-Approval 229.51, MB-Approval 229.52, Porsche C30, VW 504 00, VW 507 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: API SN, Iveco 18-1811 SC1 LV 21

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.


1 l	6	22156 ²⁶
5 l	4	22158 ²⁶
20 l	1	22160 ²⁶
60 l	1	22161 ²⁶
205 l	1	22162 ²⁶
1000 l	1	22168 ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants



SYNTHETIC MOTOR OILS LOW SAPS (LOW ASH)



Top Tec 6100 SAE 0W-30

Fully synthetic low-SAPS motor oil, designed for optimum engine and exhaust gas aftertreatment system durability and for lowest possible fuel consumption. Guarantees lowest friction and outstanding protection even under tough operating conditions in numerous BMW diesel vehicles, a variety of Mercedes-Benz vehicles as well as specific Asian and American engines. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C2, API SP, BMW Longlife-12 FE, DTFR 15D100, MB-Approval 229.61

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW 83 21 2 365 935, BMW 83 21 2 405 097, BMW 83 21 2 405 666, MB 227.1

Area of Use

Cont. Packaging Unit Part No.

1 l	6	22239	26
5 l	4	22240	26



Top Tec 4200 SAE 5W-30 New Generation



Modern fully synthetic, low-SAPS motor oil for superior performance and long engine life. Designed for use in numerous Volkswagen and Audi vehicles and also suitable for use in a variety of BMW and Mercedes-Benz diesel vehicles as well as specific Porsche models, etc. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C3, API SQ, BMW Longlife-04, MB-Approval 229.31, MB-Approval 229.51, MB-Approval 229.52, Opel OV 040 1547 - G30 / OV 040 1547 - D30, Porsche C30, VW 504 00, VW 507 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: ACEA C2, BMW Longlife-01 (up to 2018)*, BMW Longlife-01 FE (up to 2018)*, Fiat 9.55535-S1, Fiat 9.55535-S3, GWM, HAVAL, VW 500 00, VW 501 01, VW 502 00, VW 503 00, VW 503 01, VW 505 00, VW 505 01, VW 506 00, VW 506 01 (With the exception of R5 and V10 TDI engines before 6/2006), Wuling. *limited to BMW gasoline engines without particle filters in the EU including Norway, Switzerland, Great Britain and Liechtenstein

⚠ WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	2004	26
5 l	4	2011	26
20 l	1	20125	26
60 l	1	22086	26
205 l	1	22087	26
1000 l	1	22155	26



Top Tec 4500 SAE 5W-30

Modern fully synthetic, low-ash and low-friction all-season motor oil. The formulation guarantees exceptional wear protection, reduces fuel consumption while also maximizing cold start flow. Specifications met, makes this oil usable in various models from Jaguar and Land Rover as well as further vehicles equipped with diesel particulate filters (DPF).

Specifications and approvals: ACEA C1, Jaguar / Land Rover STJLR.03.5005

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Ford WSS-M2C 934-B, JASO DL-1, Mazda, Mitsubishi

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

205 l	1	22256	26
1000 l	1	22241	26



Top Tec 4600 SAE 5W-30

Modern fully synthetic, low-SAPS motor oil for superior performance and long engine life. Designed for use in a variety of BMW and Mercedes-Benz diesel vehicles and also suitable for use in several other manufacturers vehicles. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C2, ACEA C3, API SP, BMW Longlife-04, MB-Approval 229.31, MB-Approval 229.51, MB-Approval 229.52, Opel OV 040 1547 - G30 / OV 040 1547 - D30

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Fiat 9.55535-S3, Ford WSS-M2C 917-A, GM dexos2, GWM, HAVAL, Opel GM-LL-A-025, Opel GM-LL-B-025, VW 505 00, VW 505 01, Wuling

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20446	26
5 l	4	20448	26
20 l	1	20345	26
205 l	1	22151	26
1000 l	1	22175	26



Longtime High Tech SAE 5W-30

Low SAPS fully synthetic motor oil for diesel engines. Specifically developed for engines equipped with diesel particulate filters (DPF). Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C2, ACEA C3, API SP, BMW Longlife-04, MB-Approval 229.51

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Fiat 9.55535-S3, Ford WSS-M2C 917-A, MB 229.31, MB 229.52, Opel OV 040 1547 - G30 / OV 040 1547 - D30, VW 505 00, VW 505 01

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	2038	26
5 l	4	2039	26
205 l	1	22126	26
1000 l	1	22148	26

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants

SYNTHETIC MOTOR OILS LOW SAPS (LOW ASH)



Diesel High Tech SAE 5W-40

Low SAPS fully synthetic motor oil for older generation diesel engines in passenger vehicles. Specifically developed for engines equipped with diesel particulate filters (DPF).

Specifications and approvals: ACEA C3, API CF, VW 505 00, VW 505 01

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Ford WSS-M2C 917-A, VW 500 00

Area of Use

Cont. Packaging Unit Part No.

1 l	6	20006	26
5 l	4	2022	26



Top Tec 4100 SAE 5W-40


Fully synthetic low SAPS motor oil that provides exceptional protection against wear, reduced oil consumption and improved fuel consumption. Suitable for alternative fueled CNG and LPG vehicles. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C3, API SN, MB-Approval 229.31, MB-Approval 229.51, Porsche A40, VW 505 00, VW 505 01

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW Longlife-04 (up to 2018), Fiat 9.55535-H2, Fiat 9.55535-M2, Fiat 9.55535-S2, Ford WSS-M2C 917-A, GM dexos2, Renault RN 0700, Renault RN 0710

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	2329	26
5 l	4	2330	26
60 l	1	22067	26
205 l	1	22068	26



Top Tec 4110 SAE 5W-40

Top class fully synthetic, low-SAPS motor oil with the latest additive technology for superior performance and efficiency in modern gasoline and diesel vehicles with and without particulate filters (GPF / DPF). Guarantees lowest friction and outstanding protection even under tough operating conditions in high performance engines.

Specifications and approvals: ACEA C3, API SN, BMW Longlife-04, MB-Approval 229.31, MB-Approval 229.51, MB-Approval 229.52, Porsche C40, VW 511 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: GM dexos2, GWM, HAVAL, MB 226.5, Renault RN 0700, Renault RN 0710

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	22120	26
5 l	4	22122	26
20 l	1	22124	26
205 l	1	22125	26
1000 l	1	22273	26

Specifically developed for selected gasoline and diesel engines of the latest generation. Tested safe with catalytic converters and turbochargers. Depending on the manufacturer instructions, extended oil change intervals can be achieved.

1 l	6	20408	26
5 l	4	20410	26

SYNTHETIC MOTOR OILS SPECIALTIES



Special Tec LR SAE 0W-20

Fully synthetic top-of-the-line, low friction motor oil. Developed specifically for use in numerous Jaguar and Land Rover vehicles. Low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C5, API SN, Jaguar / Land Rover STJLR.51.5122

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20408	26
5 l	4	20410	26



Special Tec V SAE 0W-20

Fully synthetic superior, low friction motor oil. Developed specifically for use in various late model Volvo vehicles and also suitable for use in several other manufacturers vehicles. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA C5, API SP, Volvo VCC RBS0-2AE

⚠ WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20198	26
5 l	4	20200	26
60 l	1	20355	26
1000 l	1	22172	26



Special Tec V SAE 0W-30

Fully synthetic superior, low friction motor oil. Developed specifically for use in various late model Volvo vehicles and also suitable for use in several other manufacturers vehicles. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA A7/B7, API SL, Volvo VCC 95200377

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20202	26
5 l	4	20204	26

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants



SYNTHETIC MOTOR OILS SPECIALTIES

**Special Tec B FE SAE 0W-30**

Modern fully synthetic motor oil for superior performance and long engine life. Developed specifically for use in numerous gasoline vehicles without particulate filter (GPF) from 2002 and later. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: API SP, ACEA A5, ACEA B5, BMW Longlife-01 FE, MB-Approval 229.6, Volvo VCC 95200377

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Renault RN 0700

Area of Use

Cont. Packaging Unit Part No.

1 l	6	22260	26
5 l	4	22261	26
20 l	1	22269	26
205 l	1	22262	26
1000 l	1	22268	26

**Special Tec F SAE 0W-30**

Fully synthetic, low-SAPS motor oil for superior performance and long engine life. Designed for use in various Ford, Jaguar and Land Rover diesel and gasoline-hybrid engines, and when specifications match OE requirements. Use with extended oil change intervals as per manufacturer. For engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Specifications and approvals: ACEA C2, API SN, Ford WSS-M2C 950-A, Jaguar / Land Rover STJLR.03.5007

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: IVECO 18-1811 SC1 LV

For engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

1000 l 1 22290 26

**Special Tec F ECO SAE 5W-20**

Fully synthetic motor oil specifically designed for certain Ford Eco Boost engines. A unique additive package provides a engine clean, offers superior lubrication and supports higher fuel economy. Recommended when a Ford WSS-M2C 925-B specification is required.

Specifications and approvals: ACEA C5, API SN, Ford WSS-M2C 948-B

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Jaguar / Land Rover STJLR.03.5004

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l 6 2263 26
5 l 4 2264 26
20 l 1 20126 26
205 l 1 22115 26

**Special Tec F SAE 5W-30**

Synthetic motor oil for superior performance and long engine life. Developed specifically for use in numerous Ford and Jaguar / Land Rover gasoline and diesel engines. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA A5, ACEA B5, API SL, Ford WSS-M2C 913-D, Jaguar / Land Rover STJLR.03.5003

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Fiat 9.55535-G1, Ford WSS-M2C 913-A, Ford WSS-M2C 913-B, Ford WSS-M2C 913-C, IVECO 18-1811 S1

For gasoline and diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

1000 l 1 20848 26

**Special Tec B FE SAE 5W-30**

Modern fully synthetic motor oil for superior performance and long engine life. Developed specifically for use in numerous BMW gasoline vehicles without particulate filter (GPF) from 2002 and later. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA A5, ACEA B5, API SL

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW Longlife-01 FE

For BMW gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l 6 20442 26
5 l 4 20444 26
20 l 1 22134 26
205 l 1 22135 26
1000 l 1 22165 26

**Leichtlauf HC7 SAE 5W-40**

Low-friction, fully synthetic motor oil for all-season use in gasoline and diesel engines without particulate filters (GPF/DPF). Observe manufacturers instructions.

Specifications and approvals: ACEA A3, ACEA B4, API SN PLUS, BMW Longlife-98, MB-Approval 229.3, VW 502 00, VW 505 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Opel GM-LL-A-025, Opel GM-LL-B-025, Renault RN 0700, Renault RN 0710

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

205 l 1 22146 26
1000 l 1 22147 26

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants

MOTOR OILS SPECIALTIES



MoS₂ Antifriction SAE 10W-40

Semi-synthetic LIQUI MOLY specialty oil with an additive package containing Molybdenum Disulfide (MoS₂). The unique formulation adds a high pressure and temperature resistant lubricating layer to all friction surfaces for added wear protection and safety reserves. Reduced friction will contribute to lower oil temperatures, oil consumption and stable oil pressure. Particularly suited for older generation air or water-cooled gasoline solid lifter engines, with or without turbochargers. The MoS₂ formulation dictates the oil's gray color.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: ACEA A3, ACEA B4, API SL

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



MoS₂ Antifriction Motoroil SAE 20W-50

Mineral based LIQUI MOLY specialty oil with an additive package containing Molybdenum Disulfide (MoS₂). This unique formulation will add a high pressure and temperature resistant lubricating layer to all friction surfaces for added wear protection and safety reserves. Reduced friction will contribute to lower oil temperatures, oil consumption and stable oil pressure. Particularly suited for older generation air and water-cooled gasoline solid lifter engines, with or without turbochargers. The MoS₂ formulation dictates the oil's gray color.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: ACEA A3, ACEA B4, API SL

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SYNTHETIC MOTOR OILS ASIAN + AMERICAN (AA)



Special Tec AA SAE 0W-8

Fully synthetic premium class motor oil with ultra low viscosity, developed specifically to meet the high demands of modern Asian and American gasoline hybrid engines. Cutting edge additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with direct injection (GDI) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: JASO GLV-1

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Mazda, Toyota 08880-84112, Toyota 08880-84113



Special Tec AA SAE 0W-16

Fully synthetic premium class motor oil with extremely low viscosity, developed specifically to meet the high demands of modern Asian and American gasoline engines. Cutting edge additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with direct injection (GDI) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: API SQ, ILSAC GF-7B

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Honda, Lexus, Suzuki, Toyota



Special Tec AA SAE 0W-20

Fully synthetic low viscosity premium class motor oil, developed to meet the high demands of modern Asian and American gasoline engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with direct injection (GDI) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: API SQ, ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler MS-6395, Fiat 9.55535-CR1, Ford WSS-M2C 947-A, Ford WSS-M2C 947-B1, Ford WSS-M2C 962-A1, GM 6094 M, GM dexos1 Gen 3, Honda, Hyundai, Kia, Mazda, Mitsubishi Dia Queen, Nissan, Subaru, Toyota

Area of Use

Cont. Packaging Unit Part No.

1 l	12	2042	26
5 l	4	2043	26

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	22070	26
5 l	4	22072	26

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	22279	26
5 l	4	22280	26
20 l	1	22281	26
1000 l	1	22289	26

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20324	26
5 l	4	20328	26
20 l	1	22301	26
205 l	1	22278	26

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	2207	26
5 l	4	2208	26
20 l	1	22272	26
60 l	1	20366	26
205 l	1	20367	26
1000 l	1	22131	26

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants



SYNTHETIC MOTOR OILS ASIAN + AMERICAN (AA)



Special Tec AA SAE 5W-20

Fully synthetic low viscosity premium class motor oil, developed to meet the high demands of modern Asian and American gasoline engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with direct injection (GDI) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: API SQ, ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler MS-6395, Fiat 9.55535-CR1, Ford WSS-M2C 930-A, Ford WSS-M2C 945-A, Ford WSS-M2C 945-B1, Ford WSS-M2C 960-A1, GM 6094 M, GM dexos1 Gen 3, Honda, Hyundai, Kia, Mazda, Mitsubishi Dia Queen, Nissan, Toyota



Special Tec AA SAE 5W-30

Fully synthetic low viscosity premium class motor oil, developed to meet the high demands of modern Asian and American gasoline engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with direct injection (GDI) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: API SQ, ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler, Fiat 9.55535-CR1, Ford WSS-M2C 946-A, Ford WSS-M2C 946-B1, Ford WSS-M2C 961-A1, GM 6094 M, GM dexos1 Gen 3, GWM, HAVAL, Honda, Hyundai, Kia, Mazda, Nissan, Subaru, Toyota, Wuling



Special Tec AA SAE 5W-40 Diesel

Fully synthetic low viscosity premium class motor oil, developed to meet the high demands of modern Asian and American diesel engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with diesel particulate filters (DPF) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA E9, API CK-4, Cummins CES 20086, Ford WSS-M2C 171-F1

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar ECF-3, Chrysler MS-10902, Cummins CES 20081, Detroit Diesel DFS 93K222, Isuzu, JASO DH-2, Mack EOS-4.5, MB 228.31, Mitsubishi, MTU Typ 2.1, Nissan, Renault Trucks RLD-3, Toyota, Volvo VDS-4.5



Special Tec AA SAE 10W-30 Diesel

Fully synthetic low viscosity premium class motor oil, developed to meet the high demands of modern Asian and American diesel engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with diesel particulate filters (DPF) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA E7, E9, E11, API CK-4, Ford WSS-M2C 171-F1

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar ECF-3, Chrysler MS-10902, Cummins CES 20081, Cummins CES 20086, DAF PSQL 2.1 E, Detroit Diesel DFS 93K222, Isuzu, JASO DH-2, Mack EOS-4.5, MB 228.31, Mitsubishi, MTU Typ 2.1, Nissan, Renault Trucks RLD-3, Toyota, Volvo VDS-4.5

MOTOR OILS MOLYGEN NEW GENERATION



Molygen New Generation SAE 0W-16

Fully synthetic, extreme low viscosity LIQUI MOLY specialty with a unique additive technology. The powerful MFC (Molecular Friction Control) technology prevents formation of deposits while simultaneously reducing frictional losses. The synergistic effect provides optimum wear protection even under tough operating conditions. Improved fuel consumption and increased engine life are some of the end results. Ideally suited for engines with direct injection (GDI) and turbochargers. The oil's fluorescent green color is typical for the MFC formulation.

Specifications and approvals: API SP, ILSAC GF-6B

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Honda, Hyundai, Lexus, Suzuki, Toyota

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Area of Use

Cont.	Packaging Unit	Part No.
1 l	6	2258 <small>26</small>
5 l	4	2259 <small>26</small>
20 l	1	22292 <small>26</small>
60 l	1	20368 <small>26</small>
205 l	1	20369 <small>26</small>
1000 l	1	22166 <small>26</small>

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20136 <small>26</small>
5 l	4	20138 <small>26</small>
20 l	1	22293 <small>26</small>
205 l	1	20381 <small>26</small>
1000 l	1	22167 <small>26</small>

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

5 l	4	20426 <small>26</small>
20 l	1	20424 <small>26</small>
205 l	1	22113 <small>26</small>

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters, diesel particulate filters (DPF) and turbochargers. Observe the manufacturers instructions!

5 l	4	20440 <small>26</small>
20 l	1	20344 <small>26</small>
205 l	1	22136 <small>26</small>
1000 l	1	22137 <small>26</small>

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters, diesel particulate filters (DPF) and turbochargers. Observe the manufacturers instructions!

1 l	6	22251 <small>26</small>
5 l	4	22252 <small>26</small>

For Asian or American engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

Lubricants

MOTOR OILS MOLYGEN NEW GENERATION



Molygen New Generation SAE 0W-20

Fully synthetic LIQUI MOLY specialty with a unique additive technology. The powerful MFC (Molecular Friction Control) technology prevents formation of deposits while simultaneously reducing frictional losses. The synergistic effect provides optimum wear protection even under tough operating conditions. Improved fuel consumption and increased engine life are some of the end results. The oils fluorescent green color is typical for the MFC formulation.

Specifications and approvals: API SQ, ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler MS-6395, Fiat 9.55535-CR1, Ford WSS-M2C 947-A, Ford WSS-M2C 947-B1, Ford WSS-M2C 962-A1, GM 6094 M, GM dexos1 Gen 3, Honda, Hyundai, Kia, Mazda, Mitsubishi, Mitsubishi Dia Queen, Nissan, Subaru, Toyota

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont.	Packaging Unit	Part No.
1 l	6	20436 ²⁶
5 l	4	20438 ²⁶
205 l	1	22130 ²⁶
1000 l	1	22138 ²⁶

For Asian or American engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!



Molygen New Generation SAE 5W-20

Fully synthetic LIQUI MOLY specialty with a unique additive technology. The powerful MFC (Molecular Friction Control) technology prevents formation of deposits while simultaneously reducing frictional losses. The synergistic effect provides optimum wear protection even under tough operating conditions. Improved fuel consumption and increased engine life are some of the end results. The oils fluorescent green color is typical for the MFC formulation.

Specifications and approvals: API SQ, ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler MS-6395, Daihatsu, Fiat 9.55535-CR1, Ford WSS-M2C 930-A, Ford WSS-M2C 945-A, Ford WSS-M2C 945-B1, Ford WSS-M2C 960-A1, GM 6094 M, GM dexos1 Gen 3, Honda, Hyundai, Kia, Mazda, Mitsubishi, Mitsubishi Dia Queen, Nissan, Subaru, Toyota

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Molygen New Generation SAE 5W-30

Fully synthetic LIQUI MOLY specialty with a unique additive technology. The powerful MFC (Molecular Friction Control) technology prevents formation of deposits while simultaneously reducing frictional losses. The synergistic effect provides optimum wear protection even under tough operating conditions. Improved fuel consumption and increased engine life are some of the end results. The oils fluorescent green color is typical for the MFC formulation.

Specifications and approvals: API SQ, ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler, Chrysler MS-6395, Daihatsu, Fiat 9.55535-CR1, Ford, Ford WSS-M2C 946-A, Ford WSS-M2C 946-B1, Ford WSS-M2C 961-A1, GM 6094 M, GM dexos1 Gen 3, GWM, HAVAL, Honda, Hyundai, Isuzu, Kia, Mazda, Mitsubishi, Nissan, Subaru, Suzuki, Toyota, Wuling

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Molygen New Generation SAE 5W-40

Fully synthetic LIQUI MOLY specialty with a unique additive technology. The powerful MFC (Molecular Friction Control) technology prevents formation of deposits while simultaneously reducing frictional losses. The synergistic effect provides optimum wear protection even under tough operating conditions. Improved fuel consumption and increased engine life are some of the end results. The oils fluorescent green color is typical for the MFC formulation.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: ACEA A3, ACEA B4, API SN, BMW Longlife-01 (up to 2018), Fiat 9.55535-H2, Fiat 9.55535-N2, Fiat 9.55535-Z2, GWM, HAVAL, MB 229.5, Opel GM-LL-B-025, Porsche A40, Renault RN 0700, Renault RN 0710, VW 502 00, VW 505 00

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



Molygen New Generation SAE 5W-50

Fully synthetic LIQUI MOLY specialty with a unique additive technology. The powerful MFC (Molecular Friction Control) technology prevents formation of deposits while simultaneously reducing frictional losses. The synergistic effect provides optimum wear protection even under tough operating conditions. Improved fuel consumption and increased engine life are some of the end results. The oils fluorescent green color is typical for the MFC formulation.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: API SN

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For Asian or American engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20226 ²⁶
5 l	4	20228 ²⁶
205 l	1	20423 ²⁶
1000 l	1	22221 ²⁶

1 l	6	20230 ²⁶
5 l	4	20232 ²⁶
60 l	1	22234 ²⁶
205 l	1	20422 ²⁶
1000 l	1	22139 ²⁶

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

5 l	4	20310 ²⁶
205 l	1	22259 ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants



MINERAL MOTOR OILS



Touring High Tech SAE 10W-30

Mineral based low viscosity motor oil, particularly suited for older generation gasoline and diesel engines. Provides a stable lubricating film, keeps rubber seals such as valve stem seals, crank seals, cam seals etc. soft and pliable for low oil consumption. Designed with proven wear protection technology. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: API SF, API CD

Area of Use

Cont. Packaging Unit Part No.

5 l 4 22196 ²⁶



Touring High Tech Diesel Specialoil SAE 15W-40


Mineral based all-season motor oil, ideal for high mileage diesel vehicles without diesel particulate filters (DPF). Allows for a stable lubricating film even under extreme operating conditions. Designed with proven wear protection technology. Keeps rubber seals such as valve stem seals, crank seals, cam seals etc. soft and pliable for low oil consumption.

Specifications and approvals: ACEA A3/B4, E2, API CG-4, Allison C4, Volvo VDS

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar T0-2, Mack EO-L, MAN M 3275-1, MB 228.3, MB 229.1, MTU Typ 2

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

5 l 4 2044 ²⁶



Touring High Tech SAE 20W-50

Mineral based all-season motor oil, particularly suited for older generation high mileage gasoline and diesel vehicles. Provides a stable lubricating film even under extreme operating conditions. Designed with proven wear protection technology. Keeps rubber seals such as valve stem seals, crank seals, cam seals etc. soft and pliable for low oil consumption.

Specifications and approvals: ACEA A3/B4, E2, API SL, API CG-4, Allison C4, MIL-L 2104 E

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar T0-2, MAN 271, MB 228.3

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

5 l 4 20114 ²⁶
205 l 1 22127 ²⁶
1000 l 1 22169 ²⁶

MOTOR OILS CLASSIC CARS



Classic Motoroil SAE 20W-50 HD

High quality mineral based motor oil, developed and formulated for the specific requirements of European classic engines manufactured between 1940s to 1960s and originally equipped with an oil filter.

Specifications and approvals: API SC, API SD, API SE, API CC

For European Classic gasoline engines where a motor oil according to current specifications is required or recommended. Observe the manufacturers instructions!

5 l 4 20262 ²⁶
205 l 1 22149 ²⁶

MOTOR OILS HEAVY DUTY HD



Touring High Tech Diesel Specialoil SAE 15W-40

Mineral based all-season motor oil, ideal for high mileage diesel vehicles without diesel particulate filters (DPF). Allows for a stable lubricating film even under extreme operating conditions. Designed with proven wear protection technology. Keeps rubber seals such as valve stem seals, crank seals, cam seals etc. soft and pliable for low oil consumption.

Specifications and approvals: ACEA A3/B4, E2, API CG-4, Allison C4, Volvo VDS

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar T0-2, Mack EO-L, MAN M 3275-1, MB 228.3, MB 229.1, MTU Typ 2

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

5 l 4 2044 ²⁶



Top Tec Truck 4350 SAE 5W-30

Fully synthetic, low-SAPS premium class motor oil, developed to meet the high demands of modern heavy-duty diesel engines. The innovative additive technology and the low viscosity guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with diesel particulate filters (DPF) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA E6 E7 E8 E9 E11, API CK-4, API SN, Deutz DQC IV-18 LA, DTFR 15C100, DTFR 15C110, DTFR 15C120, Mack EOS-4.5, MAN M 3677, Renault Trucks RLD-3, Renault Trucks RXD, Scania LDF-4, Volvo VDS-4.5

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar ECF-3, Cummins CES 20086, DAF PSQL 2.1E-LD, Detroit Diesel DFS 93K22, Deutz DQC IV-10 LA, Ford WSS-M2C 213-A1, IVECO 18-1804 TLS E6, Mack EO-M Plus, Mack EO-N Plus, Mack EO-O Premium Plus, MAN M 3271-1, MAN M 3477, MAN M 3775, MB 228.31, MB 228.51, MB 228.52, MB 235.28, MTU Typ 3.1, Renault Trucks RGD, Renault Trucks RLD, Renault Trucks RLD-2, Scania Low Ash, Voith Class B, Volvo CNG, Volvo VDS-3, Volvo VDS-4

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters, diesel particulate filters (DPF) and turbochargers. Observe the manufacturers instructions!

20 l 1 22180 ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants

MOTOR OILS HEAVY DUTY HD



Top Tec Truck 4450 SAE 15W-40

Low-SAPS, premium class heavy-duty motor oil, developed specifically to meet the high demands of modern diesel engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil consumption and highest engine efficiency. Ideal for engines with diesel particulate filters (DPF) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA E9, E11, API CK-4, API SN, Cummins CES 20086, Detroit Diesel DFS 93K222, DTFR 15C100, Ford WSS-M2C 171-F1, Mack EOS-4.5, Renault Trucks RLD-3, Volvo VDS-4.5

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: ACEA E7, Caterpillar ECF-3, Cummins CES 20081, Deutz DQC III-10 LA, JASO DH-2, MAN M 3575, MAN M 3775, MB 228.31, MTU Typ 2.1



Truck Long-life Motor Oil SAE 10W-40

Premium class heavy-duty motor oil, developed specifically to meet the high demands of heavy duty diesel engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil consumption and highest engine efficiency. Ideal for engines with turbochargers without diesel particulate filters (DPF). Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA E4, ACEA E7, API CI-4, Deutz DQC III-18, DTFR 15B120 (228.5), Mack EO-N, MAN M 3277, Renault Trucks RLD-2, Renault Trucks RXD, Volvo VDS-3

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar ECF-1-a, Cummins CES 20077, Cummins CES 20078, DAF HP2, Iveco 18-1804 T3 E4, Mack EO-M Plus, MAN M 3377, MTU Typ 3, Scania LDF-2



Special Tec AA SAE 5W-40 Diesel

Fully synthetic low viscosity premium class motor oil, developed to meet the high demands of modern Asian and American diesel engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with diesel particulate filters (DPF) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA E9, API CK-4, Cummins CES 20086, Ford WSS-M2C 171-F1

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar ECF-3, Chrysler MS-10902, Cummins CES 20081, Detroit Diesel DFS 93K222, Isuzu, JASO DH-2, Mack EOS-4.5, MB 228.31, Mitsubishi, MTU Typ 2.1, Nissan, Renault Trucks RLD-3, Toyota, Volvo VDS-4.5



Special Tec AA SAE 10W-30 Diesel

Fully synthetic low viscosity premium class motor oil, developed to meet the high demands of modern Asian and American diesel engines. The innovative additive technology guarantees best wear protection and engine cleanliness, lowest oil and fuel consumption and highest engine efficiency. Ideally suited for engines with diesel particulate filters (DPF) and turbochargers. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: ACEA E7, E9, E11, API CK-4, Ford WSS-M2C 171-F1

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar ECF-3, Chrysler MS-10902, Cummins CES 20081, Cummins CES 20086, DAF PSQL 2.1 E, Detroit Diesel DFS 93K222, Isuzu, JASO DH-2, Mack EOS-4.5, MB 228.31, Mitsubishi, MTU Typ 2.1, Nissan, Renault Trucks RLD-3, Toyota, Volvo VDS-4.5

GEAR OILS



Top Tec MTF 5100 SAE 75W

Low-viscosity high-performance transmission fluid. High shear stability provides low fuel consumption and excellent wear protection. Outstanding resistance to viscosity breakdown provides superior shift performance in all operating conditions. Suitable for a variety of transmissions.

Specifications and approvals: API GL4

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW 83 22 7 533 818, BMW MTF LT-3, Fiat 9.55550-MZ6, Ford WSS-M2C 200-D2, Peugeot Citroen [B71] 2310, Toyota, Toyota 08885-81001, Toyota 08885-81081, VW G 052 178, VW G 052 512, VW G 052 726, VW G 055 512, VW G 060 726, VW G 070 726

Area of Use

Cont. Packaging Unit Part No.

5 l	4	22038	26
20 l	1	20383	26
205 l	1	22128	26
1000 l	1	22174	26

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters, diesel particulate filters (DPF) and turbochargers. Observe the manufacturers instructions!

1000 l 1 22177 26

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

5 l	4	20426	26
20 l	1	20424	26
205 l	1	22113	26

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters, diesel particulate filters (DPF) and turbochargers. Observe the manufacturers instructions!

5 l	4	20440	26
205 l	1	22136	26
1000 l	1	22137	26

For diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters, diesel particulate filters (DPF) and turbochargers. Observe the manufacturers instructions!

1 l 6 20352 26

Universal use in modern gearboxes and specific dual-clutch transmissions (DCT). Suitable for numerous BMW and Volkswagen / Audi vehicles as well as for transmissions from other manufacturers where a gear oil meeting current product specification is required or recommended. Observe the manufacturers instructions!

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants



GEAR OILS

**Top Tec MTF 5300 SAE 70W-75W**

State of the art, low-viscosity transmission fluid made with fully synthetic base oils. Provides potential fuel savings and maximum wear protection thanks to the excellent shear stability and low friction provided. Maximized shift performance in all operating conditions as a result of outstanding viscosity/temperature properties.

Specifications and approvals: API GL4

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Hyundai, Kia, VW G 052 171, VW G 052 527

Area of Use

Cont. 6 Packaging Unit Part No.

1 l 6 22274²⁶

Designed for use in modern manual and dual clutch transmissions (DSG). Recommended for Volkswagen / Audi, Hyundai, Kia, Chevrolet and many others. Observe the manufacturers instructions!

**Top Tec MTF 5400 SAE 75W-90**

Leading edge, synthetic high-performance transmission fluid. Developed to meet the severe requirements of modern transmissions and differential gears. Provides maximum wear protection thanks to its excellent shear stability and the low friction provided. Maximized shift performance in all operating conditions as a result of outstanding viscosity/temperature properties. Use with extended oil change intervals as per manufacturer.

Specifications and approvals: API GL4

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW MTF LT-4, Ford ESD-M2C 175-A, Ford ESD-M2C 186-A, Ford WSD-M2C 200-C, MB 235.72, VW 501 50, VW G 005 000, VW G 052 145, VW G 052 157, VW G 052 190, VW G 052 911, VW G 50, VW G 51

Designed for use in highly stressed manual transmissions, auxiliary drive and differential gears. Recommended for use in Volkswagen / Audi, BMW, Ford, Porsche and many others. Observe the manufacturers instructions!

1 l 6 22275²⁶

**High Performance Gear Oil (GL3+) SAE 75W-80**

Fully synthetic high-performance transmission fluid. This gear oil will deliver ideal friction to allow proper synchronizer function throughout a wide temperature range and provide ideal shift performance. Complies with a variety of manual transmission manufacturers specifications whenever a GL3 gear oil is needed. May be used when extended oil change intervals are called for.

Specifications and approvals: API GL3+

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: DAF, Eaton Extended Drain (300.000 km), IVECO, MAN 341 Typ E3, MAN 341 Typ Z3, Renault Trucks, Volvo 97305, ZF TE-ML 02D, ZF TE-ML 08

Universal use in gearboxes where a gear oil meeting the current product specification is required or recommended. Observe the manufacturers instructions.

1 l 6 22080²⁶

**High Performance Gear Oil (GL4+) SAE 75W-90**

Fully synthetic high-performance transmission fluid. Offers high shear stability combined with correct friction behavior and excellent wear protection. Outstanding resistance to viscosity breakdown provides superior shift performance in all operating conditions. Suitable for a variety of manual transmissions.

Specifications and approvals: API GL4+

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Ford ESD-M2C 175-A, VW 501 50 (G50), ZF TE-ML 08

Universal use in modern gearboxes where a gear oil meeting current product specification is required or recommended. Observe the manufacturers instructions!

1 l 6 20012²⁶
20 l 1 20014²⁶

**Gear Oil (GL4) SAE 85W-90**

Mineral based transmission oil provides accurate function at any temperature even during high torque loads. Consistent viscosity guarantees a strong lubricating film for maximum wear protection. Enables easy shifting and smooth gear engagement.

Specifications and approvals: API GL4, MIL-L 2105, ZF TE-ML 16A, ZF TE-ML 17A, ZF TE-ML 19A, ZF approval number ZF002054

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: MAN 341 Typ E1, MAN 341 Typ Z2

Universal use in gearboxes, hypoid axles and differentials without an integrated differential lock system (wet clutch) where a gear oil meeting current specifications is required or recommended. Observe the manufacturers instructions!

1 l 6 20016²⁶

**Dual Clutch Gear Oil 8100**

Fully synthetic gear oil, developed specifically to meet a variety of OE manufacturers Dual Clutch Transmission (DCT) specifications. Latest additive technology ensures superior clutch control, best shift performance and outstanding wear protection even with extended oil service intervals.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW 83 22 0 440 214, BMW 83 22 2 147 477, BMW 83 22 2 148 578, BMW 83 22 2 148 579, BMW 83 22 167 666, BMW 83 22 2 433 157, BMW DCTF-1, BMW DCTF-1+, BMW DCTF-2, BMW MTF LT-5, Chrysler, Chrysler 68044345 EA, Chrysler 68044345 GA, Eaton PS-278, Fiat 9.55550-HE2, Fiat 9.55550-MZ6, Ford 1490761, Ford 1490763, Ford F-DC, Ford KU7JM2C218AA, Ford WSS-M2C 218-A, Ford WSS-M2C 936-A, Jaguar / Land Rover GX73-M1R564-AA, MB 236.21, MB 236.22, MB 236.24, MB 239.21, MB A 000 989 04 03, MB A 000 989 20 02, Mitsubishi MZ320065 Dia-Queen SSTF-I, Peugeot Citroen (PSA) 9734.S2, Porsche 999.917.080.00, Porsche 999.917.080.01, Renault DW5, Renault DW6, Volvo 1161838, Volvo 1161839, VW G 052 182, VW G 052 529, VW G 052 536, VW G 055 529, VW G 055 536, ZF TE-ML 11

Universal use in modern dual-clutch transmissions (DCT) and gearboxes where a gear oil meeting current product specification is required or recommended. Observe the manufacturers instructions!

1 l 6 20044²⁶
5 l 4 20116²⁶
20 l 1 20046²⁶
205 l 1 22224²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants

GEAR OILS



Hypoid Gear Oil (GL5) SAE 85W-90

Mineral based gear oil provides accurate function and protection at any temperature even during high torque loads. Consistent viscosity and multifunctional EP additives guarantee a strong lubricating film for maximum wear protection.

Specifications and approvals: API GL5, DTFR 12B100 (235.0), MB-Approval 235.0, MIL-L 2105 D, ZF TE-ML 16C, ZF TE-ML 17B, ZF TE-ML 19B, ZF TE-ML 21A, ZF approval number ZF000695

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: MAN 342 Typ M1

Area of Use

Cont. Packaging Unit Part No.

1 l 6 20010 ²⁶
20 l 1 22082 ²⁶

Universal use in gearboxes, hypoid axles and differentials without an integrated differential lock system (wet clutch) where a gear oil meeting current product specification is required or recommended. Observe the manufacturers instructions!



Fully Synthetic Hypoid Gear Oil (GL5) LS SAE 75W-140

Fully synthetic hypoid gear oil, developed for use in final drives with or without wet clutch-based differentials (Limited Slip). Stable viscosity and multifunctional EP additives guarantee maximum wear protection even under extreme operating conditions. Exceeds the high requirements of well-known vehicle manufacturers and recommended for any hi-load transmission or differential in race and track vehicles or whenever added protection is needed.

Specifications and approvals: API GL5

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW rear-axle gear oil, Ford WSL-M2C 192-A, Scania STO 1:0, VME, ZF TE-ML 05D, ZF TE-ML 12D, ZF TE-ML 16G, ZF TE-ML 21D

Universal use in high-performance gearboxes, hypoid axles and differentials with and without an integrated differential lock system (wet clutch), particularly suitable for numerous BMW vehicles as well as for transmissions from other manufacturers where a gear oil meeting product specification is required or recommended. Observe the manufacturers instructions!

1 l 6 20042 ²¹
1 l 6 22178 ²⁷



Fully Synthetic Hypoid Gear Oil (GL4/5) SAE 75W-90

Fully synthetic hypoid gear oil, ideally suited for high performance applications even under extreme loads and operating conditions. Ensures maximum wear protection and promotes precise functionality over a wide temperature range and enables longer oil change intervals.

Specifications and approvals: API GL4, API GL5, API MT-1

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW 83 22 2 365 987, BMW Synthetic OSP, MB 235.8, MB 235.11, MIL-PRF 2105 E, SAE J 2360, Volvo 97312, ZF TE-ML 02B, ZF TE-ML 05A, ZF TE-ML 12L, ZF TE-ML 12N, ZF TE-ML 16F, ZF TE-ML 17B, ZF TE-ML 19C, ZF TE-ML 21A

Universal use in high-performance gearboxes, hypoid axles and differentials without an integrated differential lock system (wet clutch). Suitable for numerous BMW and Porsche vehicles as well as other manufacturers transmissions and differentials where an oil meeting current specifications is required or recommended. Observe the manufacturers instructions!

1 l 6 22090 ²⁶
20 l 1 22083 ²⁶



Multi-Disc Clutch Oil

High performance gear oil specially developed for Haldex all-wheel drive, Quattro and 4motion drives. Provides excellent viscosity and shear stability as well as outstanding friction coefficient under all operating conditions. Protects reliably against wear, foaming and corrosion. Ensures optimum power transmission on all-wheel drive vehicles.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: GM, Opel, Volvo, VW G 052 175 [TL 52175], VW G 055 175 [TL 52175-X], VW G 060 175 [TL 52175-Y]

⚠ WARNING: This product can expose you to chemicals including methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For all-wheel drive systems with Haldex coupling where a fluid according to current specifications is required or recommended to use. Observe the manufacturers instructions!

1 l 6 22194 ²⁶



Top Tec Gear EV 510

Synthetic gear oil formulated with modern additive technology for excellent aging and oxidation stability combined with maximum pressure absorption capacity. Ideally suited for high performance EV applications even under extreme loads and operating conditions. Ensures precise functionality over a wide temperature range and enables long oil change intervals.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Tesla

For use in EV high-performance transmissions where an oil meeting current specifications is required or recommended. This lubricant may be used a variation of electric vehicles including many Tesla models. Always observe manufacturers instructions!

1 l 6 22244 ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants



ATF GEAR OILS

**Top Tec ATF 1100**

Fully synthetic automatic transmission fluid with generous performance reserves. Proven additive technology provides high thermal stability, excellent wear protection and correct friction behavior. Excellent low temperature behavior. Compatible with most common seal materials.

Specifications and approvals: DTFR 13C100 (236.1), MAN 339 Typ L1, MAN 339 Typ V1, MAN 339 Typ Z1, MB-Approval 236.1, Voith H55.6335.XX (G 607), ZF TE-ML 03D, ZF TE-ML 04D, ZF TE-ML 14A, ZF TE-ML 17C, ZF approval number ZF004926

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Allison C4, Allison TES 389, Caterpillar TO-2, Dexron III G, Dexron III H, Dexron TASA (Typ A/Suffix A), Ford ESP-M2C 166-H, Ford Mercon, MB 236.6, Volvo 97341, ZF TE-ML 02F, ZF TE-ML 09, ZF TE-ML 11A, ZF TE-ML 11B, ZF TE-ML 14B

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. Packaging Unit Part No.

1 l 6 20118 ²⁶

**Top Tec ATF 1200**

Fully synthetic automatic transmission fluid with modern additive technology provides high thermal stability, excellent wear protection and correct friction behavior. Excellent low temperature behavior. Compatible with most common seal materials.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Allison C4, Allison TES 295, BMW 7045 E, BMW 8072 B, BMW LA 2634, BMW LT 71141, Caterpillar TO-2, Chrysler ATF +3, Chrysler ATF +4, Daimler NAG-1, Dexron III H, Ford Mercon V, Honda ATF Z1 (except CVT), Hyundai SP-II, Hyundai SP-III, JASO 1-A, JWS 3309 (Aisin Warner), Kia SP-II, Kia SP-III, MAN 339 Typ V1, MAN 339 Typ Z1, MAN 339 Typ Z2, Mazda ATF M-III, Mazda ATF M-V, MB 236.2, MB 236.5, MB 236.6, MB 236.7, MB 236.9, MB 236.10, MB 236.11, MB 236.91, Mitsubishi SP-II, Mitsubishi SP-III, Nissan AT-Matic D Fluid, Nissan AT-Matic J Fluid, Nissan AT-Matic K Fluid, Subaru ATF, Toyota Type T-II, Toyota Type T-IV, Voith H55.6335.XX (G 607), Volvo 97340, Volvo 97341, VW G 052 162, VW G 052 990, VW G 055 025, ZF TE-ML 02F, ZF TE-ML 03D, ZF TE-ML 04D, ZF TE-ML 05L, ZF TE-ML 09, ZF TE-ML 11A, ZF TE-ML 11B, ZF TE-ML 14A, ZF TE-ML 14B, ZF TE-ML 17C

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For automatic transmissions, manual transmissions, power steering systems and hydraulics in automotive and commercial vehicles where an ATF fluid meeting current product specification is required or recommended. Observe the manufacturers instructions!

1 l 6 20018 ²⁶
5 l 4 20020 ²⁶
20 l 1 20022 ²⁶

**Top Tec ATF 1400**

Fully synthetic transmission fluid with modern additive technology for use in late generation of Continuously Variable Transmissions (CVT) where torque transferring steel traction-chains or thrust link belts are used. A unique formulation offers best possible resistance to foaming, aging and oxidation.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Dodge CVTF+4, Dodge NS-2, Ford CVT23, Ford CVT30, Ford Mercon C, GM/Saturn DEX-CVT, Honda HCF2, Honda HMMF, Hyundai SP-CVT 1, Jeep CVTF+4, Jeep NS-2, Kia SP-CVT 1, MB 236.20, Mini Cooper [EZR 799], Mitsubishi CVTF-J1, Mitsubishi CVTF-J4, Nissan CVT NS-2 Fluid, Nissan CVT NS-3 Fluid, Subaru E-CVT, Subaru High Torque CVTF, Subaru Lineartronic CV-30, Subaru Lineartronic CVTF, Subaru Lineartronic CVTF II, Subaru NS-2, Suzuki CVT Green1, Suzuki CVT Green2, Suzuki NS-2, Suzuki TC, Toyota CVTF FE, Toyota TC, VW G 052 180, VW G 052 516

For Continuously Variable Transmissions (CVT) in automotive and commercial vehicles where a fluid meeting current specification is required or recommended. Observe the manufacturers instructions!

1 l 6 20036 ²⁶
20 l 1 20121 ²⁶

**Top Tec ATF 1600**

Fully synthetic automatic transmission fluid, developed for exclusive use in 1st generation Mercedes-Benz 7-speed automatic transmission (up to June 2010) and also compatible with various older Mercedes-Benz 5-speed automatic transmission requirements. Improved formula for sustained transmission life and maximum transmission shift performance. The fluid is a red color.

Specifications and approvals: MB-Approval 236.14

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: MB 236.12

For Mercedes-Benz automatic transmissions where an ATF fluid meeting current product specifications is required or recommended. Observe the manufacturers instructions!

1 l 6 20024 ²⁶
20 l 1 20026 ²⁶

**Top Tec ATF 1800**

Fully synthetic leading edge, high-performance automatic transmission fluid. Developed to meet the severe requirements of modern multi-speed transmissions designed with 6 or more gears. The use of modern additive technology provides ultimate protection, longer fluid life and stability combined with ideal shift quality under all operating conditions.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Aisin Warner AW-1, BMW 83 22 0 142 516, BMW 83 22 2 152 426, BMW 83 22 2 289 720, BMW 83 22 2 305 396, BMW 83 22 2 305 397, BMW 83 22 2 355 599, BMW M-1375.4, Dexron VI, Fiat 9.55550-AV5, Ford Mercon LV, Honda ATF 3.1, Honda DW-1, Honda Typ 3.0, Hyundai SP-IV, Hyundai SP-IV-RR, Isuzu ATF WSI, JASO 1A-LV, JWS 3324 (Aisin Warner), Land Rover TYK 500050, Mazda ATF FZ, MB 236.12, MB 236.14, Mitsubishi Dia Queen ATF-MA1, Mitsubishi Dia Queen ATF-PA, Nissan AT-Matic S Fluid, Nissan Matic P, Toyota WS, VW G 055 005, VW G 055 162, VW G 055 540, VW G 060 162

For modern automatic transmissions, hybrid transaxle systems and electric drive differentials where a ATF fluid meeting current product specifications is required. Observe the manufacturers instructions!

1 l 6 20032 ²⁶
5 l 4 22036 ²⁶
20 l 1 20034 ²⁶
60 l 1 22065 ²⁶
205 l 1 22056 ²⁶
1000 l 1 22173 ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Lubricants

ATF GEAR OILS



Top Tec ATF 1800 R

Fully synthetic leading edge, high-performance automatic transmission fluid. Developed to meet the severe requirements of modern multi-speed transmissions designed with 6 or more gears. The use of modern additive technology provides ultimate protection, longer fluid life and stability combined with ideal shift quality under all operating conditions. Color: red.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Aisin Warner AW-1, BMW 83 22 0 142 516, BMW 83 22 2 152 426, BMW 83 22 2 289 720, BMW 83 22 305 396, BMW 83 22 2 305 397, BMW 83 22 2 355 599, BMW M-1375.4, Dexron VI, Fiat 9.55550-AV5, Ford Mercon LV, Honda ATF 3.1, Honda DW-1, Honda Typ 3.0, Hyundai SP-IV, Hyundai SP-IV-RR, Isuzu ATF WSI, JASO 1A-LV, JWS 3324 [Aisin Warner], Land Rover TYK 500050, Mazda ATF FZ, MB 236.12, MB 236.14, Mitsubishi Dia Queen ATF-MAT1, Mitsubishi Dia Queen ATF-PA, Nissan AT-Matic S Fluid, Nissan Matic P, Toyota WS, VW G 055 005, VW G 055 162, VW G 055 540, VW G 060 162

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont.	Packaging Unit	Part No.
20 l	1	22145 ²⁶
205 l	1	22184 ²⁶
1000 l	1	22185 ²⁶



Top Tec ATF 1820

Synthetic high-performance automatic fluid, formulated with the latest base oil and additive technology. Developed to meet the severe requirements of various modern GM automatic transmissions. The superior additive technology provides ultimate protection, longer fluid life combined with ideal shift quality and lowest fuel consumption. For modern automatic transmissions, hybrid transaxle systems and electric drive differentials where an ATF fluid meeting current product specifications is required. Observe the manufacturers instructions!

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Dexron HP, GM 19300536, GM 19300537, GM 19331925, GM 19353429, GM 19353430, GMW 16974, JASO M315 Type 1A LV

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For modern GM automatic transmissions, hybrid transaxle systems and electric drive differentials where an ATF fluid meeting current product specification is required.

1 l	6	22285 ²⁶
-----	---	---------------------



Top Tec ATF 1850

Ultra-Low-Viscosity, high-performance automatic fluid. Formulated with fully synthetic base oils and the latest additive technology. Developed to meet the severe requirements of various modern 6, 8 and 10 speed automatic transmissions. The superior additive technology provides ultimate protection, longer fluid life combined with ideal shift quality and lowest fuel consumption.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Aisin Warner AW-2, BMW 83 22 2 413 477 (ATF7), Dexron ULV, Ford Mercon ULV, Ford WSS-M2C 949-A, Mazda ATF A7, PSA 16 350 560 80, Volvo 31492172, Volvo 31492173, VW G 053 001

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For modern automatic transmissions, hybrid transaxle systems and electric drive differentials where an ATF fluid meeting current product specifications is required. Observe the manufacturers instructions!

1 l	6	22257 ²¹
20 l	1	22258 ²⁶



Top Tec ATF 1900

Fully synthetic, low viscosity automatic transmission fluid, developed to meet the strict requirements of 2nd generation Mercedes-Benz 7-speed automatic transmissions (type 722.9 and 724.2 hybrid). Improved formula for sustained transmission life and maximum transmission shift performance. The fluid is a blue color.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: MB 236.15

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For Mercedes-Benz 7-speed automatic transmissions of type 722.9 and 724.2 (hybrid) where an ATF fluid meeting current product specification is required or recommended.

1 l	6	20028 ²¹
1 l	6	20360 ²⁷
20 l	1	20030 ²⁶
1000 l	1	22220 ²⁶



Top Tec ATF 1950

Fully synthetic, low viscosity automatic transmission fluid, developed to fulfill strict requirements for Mercedes-Benz 9-speed automatic transmissions (type 725.0/1). Improved formula for sustained transmission life, maximum efficiency and best transmission shift performance.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: MB 236.17

For Mercedes-Benz 9-speed automatic transmissions where an ATF fluid meeting current product specification is required or recommended. Observe the manufacturers instructions!

1 l	6	22034 ²⁶
20 l	1	22291 ²⁶
205 l	1	22296 ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

HYDRAULIC FLUIDS



Central Hydraulic System Oil

Fully synthetic central hydraulic system oil that meet and exceed many OE specifications. Unique formulation allows for high thermal stability and excellent resistance to aging or break down. Maximum wear protection and proper friction behavior. Has outstanding low temperature behavior and very high corrosion protection. The fluid is a green color.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: BMW 81 22 9 407 758, Fiat 9.55550-AG3, Ford WSS-M2C 204-A, MAN M 3289, MB 345.0, Opel 1940 766, VW G 002 000, VW G 004 000, ZF TE-ML 02K

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. Packaging Unit Part No.

1 l	6	20038 ²¹
1 l	6	20326 ²⁷
205 l	1	22187 ²⁶



Central Hydraulic System Oil 2600

LIQUI MOLY central hydraulic system oils meet or exceed demanding technical requirements and are suitable for a wide range of applications. Our unique formulations are designed around carefully selected, state-of-the-art materials that provide excellent temperature properties and guarantee accurate function even at very low temperatures. All our Central Hydraulic System oils provide the highest possible wear and corrosion protection at all temperature and pressure levels combined with optimum friction values and minimal foaming.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Chrysler MS-1872, Chrysler MS-5391, Chrysler MS-11655, Ford WSA-M2C 195-A, GM 88901975, GM 89021184, GM 9985010, GM 9985835, Hyundai PSF-3, Hyundai PSF-4, Kia PSF-3, Kia PSF-4, MB 236.3, Mitsubishi PS Fluid, Nissan PSF-II, Opel B 040 2012, Saab 30 09 800, Saab 30 32 380, Saab 93160548, Subaru K0209A0080, Toyota Type EH 008886-01, Volvo 1161529, Volvo 30741424

For power steering systems, hydropneumatic suspensions, shock absorbers, etc. where a hydraulic fluid meeting current product specification is required or recommended. Observe the manufacturers instructions!

1 l 6 22182 ²⁶



Gear Hydraulic Oil TO-4 SAE 10W

High performance, low viscosity multipurpose oil with outstanding wear protection technology. Due to the high thermal stability of the formulation the aging process is significantly reduced even at elevated temperatures. This decisively helps reduce the formation of sludge, improves cleanliness and promotes the reliability of the transmission and hydraulic system. Excellent oxidation resistance allows extended oil change intervals as per manufacturer. Specifically developed additives ensure a longer service life for wet clutches and ensure wet brakes work safely in both, low and high load conditions.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Allison C4, Caterpillar TO-4, Komatsu, ZF TE-ML 03C

Developed for construction equipment according to the high requirements of CATERPILLAR, ALLISON and KOMATSU. For power shift transmissions, transfer cases, final drives and hydraulic systems where a hydraulic oil according to current product specification is required or recommended. Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.

20 l 1 22198 ²⁶



Gear Hydraulic Oil TO-4 SAE 30

High performance multipurpose oil with outstanding wear protection technology. Due to the high thermal stability of the formulation the aging process is significantly reduced even at elevated temperatures. This decisively helps reduce the formation of sludge, improves cleanliness and promotes the reliability of the transmission and hydraulic system. Excellent oxidation resistance allows extended oil change intervals as per manufacturer. Specifically developed additives ensure a longer service life for wet clutches and ensure wet brakes work safely in both, low and high load conditions.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Allison C4, Allison TES 439, API CF, API GL4, Caterpillar TO-4, Komatsu, ZF TE-ML 03C, ZF TE-ML 07F

Developed for construction equipment according to the high requirements of CATERPILLAR, ALLISON and KOMATSU. For power shift transmissions, transfer cases, final drives and hydraulic systems where a hydraulic oil according to current product specification is required or recommended. Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.

20 l 1 22199 ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

LIQUI MOLY



PROVEN ON THE RACETRACK ...

Used by the Turner Motorsport Race Team
in their Championship winning BMWs!

... UNLEASHED ON THE STREETS.

Our full range offers the right products for every vehicle.
www.liqui-moly.com





LIQUI MOLY



Find the right Oil!

GUN CARE AT ITS FINEST BY LIQUI MOLY



Firearms need to be safe, reliable, and well-maintained. LIQUI MOLY, a German lubricant specialist, introduces the GUNTEC line, leveraging its decades of expertise in vehicle maintenance, cleaning, and care to provide the optimal solution for firearms.

Car and gun owners both face similar challenges, the need to ensure that their vehicles and firearms retain their functionality and value through regular maintenance. This applies to hunters and sport shooters, whether they use short or long guns for hunting, competition, at the shooting range, or professional use.

Proper maintenance will preserve both functionality and appearance, which is valued by everyone, from casual shooters to collectors. Consistent use of LIQUI MOLY GUNTEC products ensures safe and reliable firearms.



Lubricants

DRUM PACKAGES



Drum Packet B1

Pneumatic oil feed unit with pump nozzle

Consisting of:

- Pneumatic pump 3:1, double-action
- Intake pipe for 60 to 205 Liters
- Pump nozzle without counter
- 4 m dispensing hose 3/4"
- Maintenance unit with shutoff valve

Area of Use

Cont. 1 Piece Packaging Unit Part No.

1 Piece 1 7952 ²⁶



Drum Packet C

Pneumatic oil feed unit, movable

Consisting of:

- Pneumatic pump 3:1, double-action
- Intake pipe for 60 to 205 Liters
- Hand-held flow meter, outlet fixed at 60°
- Carriage incl. drip cup for drums up to 205 Liters
- 4 m (13') dispensing hose
- Maintenance unit with shutoff valve

1 Piece 1 7953 ²⁶



Drum Packet D

Pneumatic oil feed unit for wall mounting

Consisting of:

- Pneumatic pump 3:1, double-action
- Intake pipe for 60 to 205 Liters
- Hand-held flow meter, outlet fixed at 60°
- Hose reel, closed, 10 m (32'), 1/2 inch
- Fuel nozzle bracket
- Maintenance unit with shutoff valve

1 Piece 1 7954 ²⁶

ACCESSORIES FOR OIL PACKAGES



Trolleys for Containers/Drums

Carriage incl. drip cup for containers or drums up to 205 Liters.

1 Piece 1 7912 ²⁶

STORAGE CONTAINERS



Waste Oil Collecting Tank

with pressurized draining, 70 liters

- 2 m dispensing hose with discharge bend
- Height-adjustable collecting funnel with removable sieve
- Maximum height: 1,800 mm (6' / 72")

1 Piece 1 7810 ²⁶



Waste Oil Collection and Suction Device

with pressurized draining and vacuum extraction, 70 liters

- 2 m dispensing hose with discharge bend
- Height-adjustable collecting funnel with removable sieve
- Maximum height 1,800 mm (6' / 72")
- Sensor holder, complete with 5 suction sensors
- Adapter for BMW, Mercedes-Benz, V.A.G., PSA-Group

1 Piece 1 7828 ²⁶



Oil Drip Pan

For 2 drums up to 205 liters

- Wastewater type approval
- Dimensions: 1.200 x 800 x 360 mm (L x W x H)
- Weight: 76 kg

For environmentally friendly storage of drums.

1 Piece 1 7812 ²⁶

OTHER ACCESSORIES FOR CONTAINERS/DRUMS

**Hand Pump for Drums**

Standard pump with telescopic intake pipe for 60 to 205 Liters.

Area of Use

Cont. 1 Piece | Packaging Unit 1 | Part No. 7900²⁶**Plastic Hand Pump**

for 60 Liter and 205 Liter drums.

Plastic hand pump for drums with polypropylene telescope immersion pipe. Adjustable from 480 to 950 mm.

Can be used for nearly all low viscosity fluids. Do not use to pump Hazard Class A I and A II solvents and fluids.

1 Piece | 1 | 7932²⁶

GEAR OIL FILLER

**Hand Pump**

Hand pump supplied with universal hose, metric to U.S. thread adapter for easy filling of outboard engines, transmissions, differentials and other units. Universal use on lawnmowers, ride-on mowers, snow blowers, motorcycle engines and transmissions etc. Fits all LIQUI MOLY 1 Liter containers.

For filling transmissions and other units such as outboard motors, lawnmowers, emergency power units, riding mowers, snow blowers or motorcycle transmissions.

1 Piece | 1 | 29026¹⁵²**Oil Filling Unit for Transmissions**

- Tank volume: 7 Liters
- Filling hose: 1,600 mm (5.2' / 63")
- includes 16 adapter for BMW, Ford, Mercedes-Benz, Volkswagen, etc.
- Drip pan


For filling transmissions and differentials with oil. Specifically for dual-clutch transmissions.

1 Piece | 1 | 7941²⁶

DRAIN TAP AND OIL CHANGE ACCESSORIES

**Drain Cock With Seal for 20L Jugs (PVC-Viton)**

For 20 Liter canister. Plastic DIN 61 thread

1 Piece | 1 | 7924²⁶**Sealing Rings (4 Pieces)**

Spare seals for the drain cock, part no. 7924.

1 Piece | 1 | 29130²⁶**3/4" Ball Drain Faucet**

For 50, 60 and 205-liter drums, with 3/4" thread.

1 Piece | 1 | 3329²⁶

Lubricants

DRAIN TAP AND OIL CHANGE ACCESSORIES



Drain Cock 3/4" a

For 50, 60 and 205-liter drums, with 3/4" thread.

Area of Use

Cont. 1 Piece

Packaging Unit

Part No.

1 Piece 1 3323 ²⁶



Protective Caps for Drain Cocks (4 Pieces)

Protect drain cocks from damage and soiling. With safety tab to protect against loss. The protection caps prevent the ingress or leakage of liquids within certain limits. Suitable for part no. 3323, part no. 7924 and part no. 29076.

1 Piece 1 29540 ²⁶



Drain Cock in Brass

For 50 l, 60 l and 205 l drums with 3/4" thread.

1 Piece 1 3385 ²⁶



Oil and Chemical Binder Plus

10 kg 1 21928 ²⁶

ADDITIVE PUMPS



Hand Drum Pump

for 50-liter additive drums

- Stainless steel hand pump with Teflon seals
- Delivery rate 0.25 Liter per stroke

For pumping low-viscosity acids and bases, neutral, aggressive and non-flammable liquids from 50-60 Liters drums.

1 Piece 1 7928 ²⁶

BRAKE FLUID CHANGE



Brake Fluid xTronic

The Brake Fluid xTronic was designed with the professional workshop in mind and allows a technician to perform the entire brake fluid exchange with quick turnaround times and maximum efficiency. It is compatible for vehicles equipped with or w/o ABS, ESP, EDS, SBC, etc. systems, the pulsating fluid flow efficiently removes air bubbles from the hydraulic system. It is therefore the perfect all-round solution for quick and professional flushing and brake fluid changes.

For more detailed information, refer to the operating manual or LIQUI MOLY video. Professional, trained personnel use only.

1 Piece 1 29350 ²¹

PAINT



Scratch Stop

A silicone free polishing paste suitable for universal use. The product can be used to remove scratches, overspray, swirl marks and uneven finish on solid or metallic paintwork. It is also suitable for matt plastic parts as well as polycarbonate headlight lenses, and can be applied either manually or with a buffer.

⚠ WARNING: This product can expose you to chemicals including formaldehyde, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. Packaging Unit Part No.

200 ml 12 20384 ²⁶

GLASS



Windshield Washer Fluid Concentrate Lemon

Special concentrate for use in non-freezing temperatures. Provides a clear, smear-free view in seconds. Removes oil, silicone films and insect residue. With citrus cleaning power. Phosphate-free and biodegradable. Mixture 1:100.

Suitable for use with polycarbonate and most other common materials.

20 ml 50 20388 ²¹

INTERIOR



Leather Care

A mix of carefully selected ingredients natural and synthetic, prevent smooth leather from becoming brittle with age. Leather Care cleans as well as preserves by adding a silky protective layer on new or used leather. Excellent leather care lotion for auto, motorcycle gear and furniture. Smooth leather regains elasticity and softness when treated. Formulated with a mixture of waxes and other carefully selected care products.

⚠ WARNING: This product can expose you to chemicals including 1,4-dioxane, which is known to the State of California to cause cancer and ethylene oxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Specifically developed for maintaining automotive leather upholstery but may be used to treat smooth leather in other areas such as motorcycle gear and furniture, hand bags, luggage or clothing. Not suitable for suede.

250 ml 6 20394 ²¹
250 ml 6 22230 ²⁷



Car Interior Cleaner

Quick, effective and strong yet gentle cleaning of plastic and fabrics as well as interior trim. Thoroughly removes oil, grease, nicotine and other grime. Easily removes beverage spills, candy stains and nicotine residue.

⚠ WARNING: This product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use on most common vehicle interior materials.

500 ml 6 20392 ²⁶

ACCESSORIES



Tornador Gun

Developed as a touchless, easy-to-use device for easy cleaning of hard or soft surfaces. Suitable for vehicle interior and exterior cleaning. Air operated. The air/cleaner mixture is automatically atomized and rotated at high speed for an effective and easy cleaning. The distinctive tornado effect easily removes dirt and grime within a short duration.

To remove contamination on floor mats, upholstery and seats, stowage compartments, door hinges, etc. Do not add any other liquids than Universal Cleaner (Part no. 20396). Store completely empty.

1 Piece 1 29077 ²⁶

CLEANER



Universal Cleaner

Concentrated degreaser and industrial cleaner for dilution with water. Phosphate, silicate and solvent-free. Ideal for cleaning of walls and floors and may be used with high-pressure washers. Unique, highly effective biodegradable surfactants make Universal Cleaner ideal as a replacement for many environmentally harmful degreasers.

Thanks to its high effectiveness, it is suitable for universal use in households, workshops and industry.

1 l 6 20396 ²¹

Service Products



Brake & Parts Cleaner

The combination of select acetone free solvents provides quick and efficient removal of grease and dirt from contaminated surfaces and can be used in automotive and industrial applications as well as in other industries. Thanks to its low surface tension it will easily penetrate into and behind deposits like oil, grease and sticky substances to completely dissolve these, even in hidden areas. Once evaporated it will leave behind a dry, grease and oil free surface.

Area of Use

Cont. Packaging Unit Part No.

500 ml 12 22188 ²¹



Brake & Parts Cleaner

The combination of select acetone free solvents provides quick and efficient removal of grease and dirt from contaminated surfaces and can be used in automotive and industrial applications as well as in other industries. Thanks to its low surface tension it will easily penetrate into and behind deposits like oil, grease and sticky substances to completely dissolve these, even in hidden areas. Once evaporated it will leave behind a dry, grease and oil free surface.

Universal cleaner for rapid cleaning and degreasing of small components in the automotive and industrial sector. For brakes, clutches, transmissions, and for fitting and repair work. Removes oil and grease spots from floor coverings, materials and linings. Not for sale in the following states: CA, CO, CT, DE, IL, IN, MD, MA, ME, MI, NJ, NH, NY, OH, PA, RI, UT, VA, WA. May not be legal for use or sale in other areas. Check local regulations.

196 l 1 22236 ²¹



Pump Spray Bottle

Spray bottle with hand pump. For the application of numerous chemicals. For universal used thanks to the sealing material Viton with its high chemical resistance. Capacity: 0.9 l cleaning fluid.

Universal cleaner for rapid cleaning and degreasing of small components in the automotive and industrial sector. For brakes, clutches, transmissions, and for fitting and repair work. Removes oil and grease spots from floor coverings, materials and linings. Not for sale in the following states: CA, CO, CT, DE, IL, IN, MD, MA, ME, MI, NJ, NH, NY, OH, PA, RI, UT, VA, WA. May not be legal for use or sale in other areas. Check local regulations.

1 l 1 3316 ²⁶



Screw Retainer Medium Strength

Optimum thread locking product for use on threads up to $\frac{3}{4}$ " and most fastener materials. May be applied to oily surfaces. Prevent threaded fastener loosening due to shock or vibration.

Use on fasteners in various applications - automotive, industrial, Farming, home etc. Before use confirm compatibility with fastener material. Apply uniformly onto threads. Product cures when confined in the absence of air between close fitting surfaces. Rate of cure will depend on material.

10 g 6 22226 ²⁶



Screw Retainer High Strength

Optimum thread locking product for use on threads up to $\frac{3}{4}$ " and most fastener materials. May be applied to oily surfaces. Prevent threaded fastener loosening due to shock or vibration.

Use on fasteners in various applications - automotive, industrial, Farming, home etc. Before use confirm compatibility with fastener material. Apply uniformly onto threads. Product cures when confined in the absence of air between close fitting surfaces. Rate of cure will depend on material.

10 g 6 22228 ²⁶



ADDITIVES



Motorbike Engine Flush

A highly effective formulation for quick and safe removal of deposits from engines before an oil change. A clean engine will provide less wear, lower emissions and improved performance while preventing premature oil degradation.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. Packaging Unit Part No.

250 ml 6 **20050** ²¹
250 ml 6 **22098** ²⁷



Motorbike 4T Bike-Additive

Removes deposits from the fuel system, valves, spark plugs and the combustion chamber while preventing new deposit formation. Improves engine performance and lowers emissions. Provides corrosion protection throughout and prevents carburetor icing.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for all 4-stroke engines, with or without wet clutches. Safe with catalytic converters. One full can (250 ml) used with 3-4.5 Liters (3.2 to 4.8 U.S. Qts) of motor oil.

125 ml 6 **20048** ²¹
125 ml 6 **22096** ²⁷



Motorbike Speed Additive

A unique, state-of-the-art combination of acceleration-enhancing, cleaning, dispersing and material-protecting additives. Easy engine start, smoother running and better throttle response are the effects.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters. Contents (150 mL) is sufficient for 15-20 Liters (4 gal. to 5.3 gal.) gasoline.

150 ml 6 **20108** ²¹
150 ml 6 **22104** ²⁷



Motorbike Gasoline Stabilizer

Preserves fuel and protects against premature aging and oxidation during long term storage. Prevents corrosion in fuel system and increases operational reliability of 2- and 4-stroke engines in motor scooters, ATVs, snowmobiles etc. during long-term storage.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters. Use 25 mL dosage with 5 Liters (1.3 gal.) of fuel.

250 ml 6 **20052** ²¹
250 ml 6 **22102** ²⁷

MOTOR OILS 4-STROKE STREET



Motorbike 4T Synth 5W-40 Street Race

Fully synthetic high-performance motor oil, developed and tested on racing machines. Ensures maximum performance and protection even in extreme operating conditions. Provides maximum engine cleanliness with reduced friction and minimum wear, smooth clutch operation, and effortless gear shift resulting in complete riding satisfaction!

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20074	²⁶
4 l	4	20076	²⁶
20 l	1	20304	²⁶
60 l	1	2593	²⁶
205 l	1	2594	²⁶



Motorbike 4T Synth SAE 10W-50 Street Race

Fully synthetic high-performance motor oil, developed and tested on racing machines. Ensures maximum performance and protection even in extreme operating conditions. Provides maximum engine cleanliness with reduced friction and minimum wear, smooth clutch operation, and effortless gear shift resulting in complete riding satisfaction!

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20066	²⁶
4 l	4	20068	²⁶
20 l	1	20305	²⁶
60 l	1	1564	²⁶
205 l	1	1569	²⁶

MOTOR OILS 4-STROKE STREET



Motorbike 4T Synth SAE 10W-60 Street Race

Fully synthetic high-performance motor oil, developed and tested on racing machines. Ensures maximum performance and protection even in extreme operating conditions. Provides maximum engine cleanliness with reduced friction and minimum wear, smooth clutch operation, and effortless gear shift resulting in complete riding satisfaction!

Specifications: API SP, JASO MA2

Area of Use

Cont. Packaging Unit Part No.

1 l	6	20070	26
4 l	4	20072	26
20 l	1	20303	26
60 l	1	2724	146

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!



Motorbike 4T SAE 10W-40

High quality mineral-based motor oil for ideal behavior and engine protection in all operating conditions. Provides reliable lubrication, optimum noise suppression and low wear together with perfect clutch function and smooth shifting.

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20190	26
4 l	4	20192	26
20 l	1	20194	26
60 l	1	22063	26
205 l	1	22064	26



Motorbike 4T SAE 5W-40 HC Street

Fully synthetic high-performance motor oil provides optimum performance and engine protection in all operating conditions. Ensures outstanding engine cleanliness, excellent friction behavior and minimum wear together with perfect clutch operation, and smooth gear shifting.

Specifications and approvals: API SN PLUS, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20412	26
4 l	4	20414	26
20 l	1	20416	26
60 l	1	22043	26
205 l	1	22069	26



Motorbike 4T SAE 10W-30 Street

Fully synthetic high-performance motor oil provides optimum performance and engine protection in all operating conditions. Ensures outstanding engine cleanliness, excellent friction behavior and minimum wear together with perfect clutch operation, and smooth gear shifting.

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20418	26
4 l	4	20420	26
20 l	1	20417	26
60 l	1	22059	26
205 l	1	22060	26



Motorbike 4T SAE 10W-40 Street

Fully synthetic high-performance motor oil provides optimum performance and engine protection in all operating conditions. Ensures outstanding engine cleanliness, excellent friction behavior and minimum wear together with perfect clutch operation, and smooth gear shifting.

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20054	26
4 l	4	20056	26
20 l	1	20302	26
60 l	1	22054	26
205 l	1	22055	26



Motorbike 4T SAE 15W-50 Street

Fully synthetic high-performance motor oil provides optimum performance and engine protection in all operating conditions. Ensures outstanding engine cleanliness, excellent friction behavior and minimum wear together with perfect clutch operation, and smooth gear shifting.

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20058	26
4 l	4	20060	26
20 l	1	22300	26
60 l	1	22061	26
205 l	1	22062	26

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

MOTOR OILS 4-STROKE STREET



Motorbike 4T SAE 20W-50 Street

High quality mineral-based motor oil for ideal behavior and engine protection in all operating conditions. Provides reliable lubrication, optimum noise suppression and low wear together with perfect clutch function and smooth shifting.

Specifications: API SP, JASO MA2

Area of Use

Cont. Packaging Unit Part No.

1 l	6	20062	26
4 l	4	20064	26
20 l	1	22116	26
60 l	1	22117	26
205 l	1	22176	26

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!



Motorbike HD Synth SAE 20W-50 Street

Fully synthetic motor oil specifically recommended for certain Harley-Davidson engines, primary drives and transmissions, among others. The high-quality formulation ensures excellent resistance to wear and thermal stress even under extreme operating conditions. Optimum lubrication, excellent engine cleanliness and the best wear protection are therefore guaranteed.

Specifications: API SP, JASO MA2

Liqui Moly recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Harley-Davidson H-D 360 Motor Cycle Oil 62600042

Harley-Davidson specific oil usable in 4-stroke engines, certain primary drives and transmissions with or without wet clutches where a fluid meeting current product specification is required. Observe the manufacturers instructions!

1 l	6	20100	26
4 l	4	20102	26
20 l	1	22118	26
60 l	1	22119	26

MOTOR OILS 4-STROKE OFFROAD



Motorbike 4T Synth SAE 10W-50 Offroad Race

Fully synthetic high-performance motor oil, developed and tested on racing machines. Ensures maximum performance and protection even in extreme operating conditions. Provides maximum engine cleanliness, reduced friction and minimum wear with smooth clutch operation, and effortless gear shift resulting in complete riding satisfaction!

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20078	26
4 l	4	20080	26
20 l	1	20307	26



Motorbike 4T Synth SAE 10W-60 Offroad Race

Fully synthetic high-performance motor oil, developed and tested on racing machines. Ensures maximum performance and protection even in extreme operating conditions. Provides maximum engine cleanliness, reduced friction and minimum wear with smooth clutch operation, and effortless gear shift resulting in complete riding satisfaction!

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20186	26
4 l	4	20188	26
20 l	1	20195	26



Motorbike 4T SAE 10W-40 Offroad

Fully synthetic high-performance motor oil provides optimum performance and engine protection in all operating conditions. Ensures outstanding engine cleanliness, excellent friction behavior and minimum wear together with perfect clutch operation, and smooth gear shifting.

Specifications: API SP, JASO MA2

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20082	26
4 l	4	20084	26
20 l	1	20306	26

MOTOR OILS 2-STROKE OFFROAD



Motorbike 2T Synth Offroad Race

Fully synthetic high-performance 2-stroke motor oil developed and tested on racing machines. Ensures maximum performance and protection of the engine in all operating conditions. Outstanding lubrication and engine cleanliness, excellent friction behavior and minimized wear as well as less smoke. This oil improves the riding experience!

Specifications and approvals: API TC, Husqvarna, ISO L-EGD, JASO FD

For air or water cooled 2-stroke gasoline engines where an oil according to current product specifications is required or recommended. Self-mixing. Pre-mix applications up to 1:100 ratio and according to the manufacturers instructions. Observe the manufacturers instructions!

1 l	6	20178	26
4 l	4	20180	26

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

MOTOR OILS 4-STROKE ATV/SXS



ATV 4T Motoroil SAE 5W-50

Fully synthetic high-performance motor oil, developed and tested on racing machines. Ensures maximum performance and protection even in extreme operating conditions. Provides maximum engine cleanliness, reduced friction and minimum wear with smooth clutch operation, and effortless gear shift resulting in complete riding satisfaction!

Specifications and approvals: API SN PLUS, JASO MA2

Area of Use

Cont. Packaging Unit Part No.

1 l	6	20212	26
4 l	4	20214	26
20 l	1	22299	26

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

MOTOR OILS 4-STROKE SNOWMOBILE



Snowmobile Motoroil SAE 0W-40

Fully synthetic low-friction motor oil designed for quick lubrication on cold start. The combination of high quality synthetic base oils together with an advanced additive package produces a low viscosity motor oil with high shear stability. This high-quality blend prevents engine deposits. Engine wear is reduced to a minimum thanks to low friction and heat.

Specifications and approvals: ACEA A3, ACEA B4, API SN, API CF

For 4-stroke snowmobile engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20148	26
4 l	4	20150	26
205 l	1	22129	26

MOTOR OILS 4-STROKE SNOWBIKE



Snowbike Motor Oil SAE 0W-40

Fully synthetic low-friction motor oil designed for quick lubrication on cold start. The combination of high quality synthetic base oils together with an advanced additive package produces a low viscosity motor oil with high shear stability. This high-quality blend prevents engine deposits. Engine wear is reduced to a minimum thanks to low friction and heat.

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: API SN, JASO MA2

⚠ WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For 4-stroke Snowbike engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters. Observe the manufacturers instructions!

1 l	6	20356	26
4 l	4	20358	26

GEAR OILS



Motorbike Gear Oil SAE 75W-90

Fully Synthetic, GL5 high-performance extreme-pressure gear oil. Facilitates smooth and precise shifting even in extreme conditions, provides excellent wear protection properties and ideal viscosity-temperature behavior.

Specifications and approvals: API GL5, MIL-L 2105 C, MIL-L 2105 D

Universal use in motorbike transmissions and final drives where a gear oil according to current product specifications is required or recommended. Observe the manufacturers instructions!

1 l	6	20086	26
-----	---	-------	----



Motorbike Gear Oil SAE 75W-140 (GL5)

Fully Synthetic, GL5 high-performance extreme-pressure gear oil. Facilitates smooth and precise shifting even in extreme conditions, provides excellent wear protection properties and ideal viscosity-temperature behavior.

Specifications and approvals: API GL5

Universal use in motorbike transmissions and final drives where a gear oil according to current product specifications is required or recommended. Observe the manufacturers instructions!

1 l	6	20088	26
-----	---	-------	----

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

FORK OILS/SHOCK ABSORBER OILS



Motorbike Fork Oil SAE 5W Light

Full synthetic, low-viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

Area of Use

Universal use in telescopic forks and shock absorbers on motorbikes and other power-sport vehicles where an oil with current product specifications is required or recommended. Observe the manufacturers instructions!

Cont. 1 l 6 20094²¹
1 l 6 22108²⁷
20 l 1 20402²⁶



Motorbike Fork Oil SAE 7,5W Medium/Light

Full synthetic, medium/light viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

Universal use in telescopic forks and shock absorbers on motorbikes and other power-sport vehicles where an oil with current product specifications is required or recommended.

1 l 6 20098²⁶
20 l 1 20403²⁶



Motorbike Fork Oil SAE 10W Medium

Full synthetic, medium-viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

Universal use in telescopic forks and shock absorbers on motorbikes and other power-sport vehicles where an oil with current product specifications is required or recommended. Observe the manufacturers instructions!

1 l 6 20092²⁶
20 l 1 20404²⁶



Motorbike Fork Oil SAE 15W Heavy

Full synthetic, high-viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

Universal use in telescopic forks and shock absorbers on motorbikes and other power-sport vehicles where an oil with current product specifications is required or recommended. Observe the manufacturers instructions!

1 l 6 20096²⁶
20 l 1 20405²⁶



Motorbike Shock Absorber Oil Race

Fully synthetic shock absorber oil. Prevents deposit build-up while reducing friction and wear. Foaming is prevented even during extreme conditions. The unique formulation allows better handling and rider feedback which allows easier suspension tuning. Fluid color is blue.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Designed for racing or extreme motorbike and power-sports use and when a fluid according to current product specifications is required or recommended. Observe the manufacturers instructions!

1 l 6 20290²⁶
20 l 1 20292²⁶



Motorbike Shock Absorber Oil

Mineral based shock absorber oil. Prevents deposit build-up while reducing friction and wear. Foaming is prevented even during extreme conditions. The unique formulation allows better handling and rider feedback which allows easier suspension tuning.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Universal use in telescopic forks and shock absorbers on motorbikes and other power-sport vehicles where an oil with current product specifications is required or recommended. Observe the manufacturers instructions!

1 l 6 20294²⁶
20 l 1 20293²⁶

MAINTENANCE PRODUCTS



Motorbike Visor Cleaner

Maintains and cleans helmets and visors. Active anti-fog treatment for glass or plastic visors. With long-lasting effect. Removes dirt, insects, oil and silicone films. Provides clear vision and safety.

WARNING: This product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Universal use for cleaning, care and anti-fogging of glass and plastic visors. Test visor to be cleaned for compatibility. Spray fluid onto surface, allow it to take effect and remove with a damp cloth or sponge. Do not use on hot surfaces.

100 ml 12 20160²¹
100 ml 12 22170²⁷

MAINTENANCE PRODUCTS



Motorbike Chain Lube

Fully synthetic chain grease, extremely adhesive and water resistant. Excellent creep ability and lubrication behavior. Extremely effective and lasting on high-speed chains. Provides increased chain life and reduced elongation.

WARNING: This product can expose you to chemicals including n-hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. Packaging Unit

Part No.

400 ml 12 **20162** ²⁷
400 ml 12 **20350** ²¹



Hand Pump

Hand pump supplied with universal hose, metric to U.S. thread adapter for easy filling of outboard engines, transmissions, differentials and other units. Universal use on lawnmowers, ride-on mowers, snow blowers, motorcycle engines and transmissions etc. Fits all LIQUI MOLY 1 Liter containers.

Fully synthetic formulation for initial lubrication or maintenance of drive chains. Excellent for use in dusty, dirty and corrosive operating conditions. For high load- and high-speed chains with and without O/X-rings.

1 Piece 1 **29026** ²⁶



Oil Filling Unit for Transmissions

- Tank volume: 7 Liters
- Filling hose: 1,600 mm (5.2' / 63")
- includes 16 adapter for BMW, Ford, Mercedes-Benz, Volkswagen, etc.
- Drip pan

For filling transmissions and other units such as outboard motors, lawnmowers, emergency power units, riding mowers, snow blowers or motorcycle transmissions.

1 Piece 1 **7941** ²⁶

Marine



ADDITIVES

**Marine Gasoline Stabilizer Shooter**

Provides long-term protection against fuel aging and oxidation. Protects fuel system from corrosion and prevents problems during long term storage. When added to gasoline it uses its organic content to stabilize the fuel.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont. 200 ml 20 25100 ²¹

**Marine 4T Shooter**

An effective mixture of additives that clean and maintain fuel systems of port injected and carbureted gasoline engines. Cleans injectors, combustion chamber and protects against corrosion. Restores proper fuel atomization and improves engine efficiency. Regular use keeps the fuel system in perfect working order.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for all 2- stroke and 4-stroke engines. Safe with catalytic converters. Contents (200 ml) is sufficient for 50–70 Liters (13 gal. to 18 gal.) fuel.

200 ml 20 25102 ²¹

**Marine Super Diesel Additive**

A combination of additives that clean and maintain diesel fuel systems. Prevents corrosion and increases lubrication thus reducing fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order. Protects against the negative effects of too high proportion of water in fuel systems.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use in all 4-stroke gasoline engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF). Contents (200 ml) is sufficient for 50–70 Liters (13 gal. to 18 gal.) fuel.

500 ml 6 20526 ²⁷
500 ml 6 20550 ²¹
1 l 6 20552 ²¹

**Marine Gasoline Stabilizer**

Provides long-term protection against fuel aging and oxidation. Protects fuel system from corrosion and prevents problems during long term storage. When added to gasoline it uses its organic content to stabilize the fuel.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Suitable for use with HVO / XTL Diesel fuel. To be added directly into the fuel tank, ideal for long-term use with every refueling. 500 ml is sufficient for up to 250 Liters (66 gal.) / 1 Liter is sufficient for up to 500 Liters (132 gal.) diesel fuel (mixing ratio up to 1: 500).

1 l 6 20502 ²¹

**Marine Gasoline System Cleaner**

An effective mixture of additives used to clean and maintain fuel systems of injected or carbureted Marine gasoline engines. Prevents corrosion, cleans injectors and the combustion chamber, restores proper fuel atomization and improves engine efficiency. Suitable for use as problem solver as well as for preventive maintenance. Protects against the negative effects of too high proportion of water in fuel systems.

WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Suitable for all 2- stroke and 4-stroke engines. Safe with catalytic converters. Filling the dosage chamber once is sufficient for 5 liters (5.25 U.S. QT) of fuel (mixing ratio 1: 200).

500 ml 6 20504 ²¹

GREASES

**Marine Grease**

A high-performance lubricant appropriate for a variety of marine usage. Reduces friction and wear. High shear stability provides excellent resistance to aging. Cold and hot water resistant, water repellent and saltwater resistant. Long lasting in wet environments while providing excellent sealing properties. Meets the requirements of NATO Marine Specification G460. Certification DIN 51502. KPF2G-20.

WARNING: This product can expose you to chemicals including arsenic, which is known to the State of California to cause cancer and lead which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Universal marine use most anywhere grease is needed for lubrication. May be used on equipment being exposed to salty air and ocean water. Observe the manufacturers instructions!

250 g 12 20540 ²⁶
400 g 12 20542 ²⁶

GREASES



Marine Winch Grease



A synthetic high-performance grease enhanced with solid PTFE solid-lubricants. Specifically developed for use on winches and hoists. The solid lubricant provides the ultimate in wear protection and friction reduction. Resistant to seawater and freshwater and with excellent adhesive properties. Does not contain resins or acids and does not affect non-ferrous metals or plastics. Certification DIN KHF1N-35.

Area of Use

Cont. Packaging Unit Part No.

100 g 6 20524 26

Particularly suited for winches and hoists with non-ferrous metal pairings and plastic/metal pairings. Saltwater resistant. Observe the manufacturers instructions!

MOTOR OILS 4-STROKE



Marine 4T Motor Oil SAE 10W-30

Fully synthetic, high-performance low-friction motor oil formulated with specific marine additives for increased corrosion and wear protection. Ideal properties for either on board or outboard gasoline engines. Allows fast penetration on start up. With optimum wear protection. Exceeds major manufacturers requirements.

Specifications and approvals: API SM, NMMA FC-W Catalyst Compatible®

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Honda Marine, Mercury Marine, NMMA FC-W, Selva, Suzuki Marine, Tohatsu, Volvo Penta, Yamaha

For 4-stroke gasoline engines, where a motor oil according to current product specifications is required or recommended. Safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20520	26
4 l	4	20522	26
20 l	1	20495	26
60 l	1	25025	26
205 l	1	25074	26



Marine 4T Motor Oil SAE 10W-40

Fully synthetic, heavy duty motor oil. Provides outstanding wear protection, proper oil pressure and engine cleanliness. Optimum protection of engine components thanks to high content of anti-corrosion additives. Developed specifically for marine use. Meets major manufacturers requirements.

Specifications and approvals: ACEA A3/B4, E7, API SL, API CI-4, Mack EO-N, Renault Trucks RLD-2, Volvo VDS-3

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Caterpillar ECF-1-a, Caterpillar ECF-2, Cummins CES 20071, Cummins CES 20072, Cummins CES 20076, Cummins CES 20077, Cummins CES 20078, Detroit Diesel, Deutz DQC III-10, MAN M 3275-1, Mercury Marine, MTU Typ 2, Selva, Suzuki Marine, Tohatsu, Yamaha

For 4-stroke gasoline engines, where an oil according to current product specifications is required or recommended. Safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20506	26
4 l	4	20508	26
20 l	1	20494	26
60 l	1	20497	26
205 l	1	20498	26



Marine PWC Oil SAE 10W-40

Fully synthetic high performance motor oil for PWCs. The special additive package ensures maximum engine performance and ideal wear protection. Guarantees the best possible lubrication, outstanding engine cleanliness and excellent friction values for wet clutches, even at high speeds. Meets or exceeds the requirements and specifications of major manufacturers.

Specifications: API SP, JASO MA2

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Honda, Kawasaki, SeaDoo, Suzuki, Yamaha

For 4-stroke gasoline PWC engines with or without wet clutches, where an oil according to current product specifications is required or recommended. Safe with catalytic converters, turbochargers and superchargers. Observe the manufacturers instructions!

1 l	6	20528	26
4 l	4	20530	26
20 l	1	22525	26
60 l	1	22518	26
205 l	1	22519	26



Marine 4T Motor Oil SAE 15W-40 New Generation

Low-SAPS, premium class motor oil, developed specifically to meet the high demands of modern Marine diesel engines. The innovative additive technology guarantees best wear protection, outstanding corrosion protection and engine cleanliness, lowest oil consumption and highest engine efficiency. Ideal also for engines with diesel particulate filters (DPF) and turbochargers.

Specifications and approvals: ACEA E9, E11, API CK-4, API SN, Cummins CES 20086, Detroit Diesel DFS 93K222, Mack EOS-4.5, Renault Trucks RLD-3, Volvo VDS-4.5

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: ACEA E7, Caterpillar ECF-3, Deutz DQC III-10 LA, JASO DH-2, MAN M 3575, MTU Typ 2.1

For Marine diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters, diesel particulate filters (DPF) and turbochargers. Observe the manufacturers instructions!

4 l	4	22520	26
20 l	1	22522	26
205 l	1	22523	26



Marine 4T Motor Oil SAE 25W-40

High performance motor oil formulated with specific synthetic marine additives. Provides a stable lubricating film and best wear protection in the most extreme conditions. Maintains engine rubber seals for lowest possible oil consumption.

Specifications and approvals: API SM, NMMA FC-W Catalyst Compatible®

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Honda Marine, Mercury Marine, NMMA FC-W, Selva, Suzuki Marine, Tohatsu, Volvo Penta, Yamaha

For 4-stroke gasoline engines, where an oil according to current product specifications is required or recommended. Safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	20546	26
4 l	4	20548	26
20 l	1	20497	26
60 l	1	25029	26
205 l	1	25057	26



For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

Marine



MOTOR OILS 4-STROKE



Marine 4T Motor Oil SAE 25W-50

Heavy-duty motor oil formulated with specific synthetic marine additives. Provides a stable lubricating film and best wear protection in the most extreme conditions. Maintains engine rubber seals for lowest possible oil consumption.

Specifications and approvals: API SM, NMMA FC-W Catalyst Compatible®

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Mercury Marine, NMMA FC-W

⚠ WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Area of Use

Cont.	Packaging Unit	Part No.
1 l	6	22508 ²⁶
4 l	4	22510 ²⁶
205 l	1	22514 ²⁶



Marine Single Grade SAE 30

Mineral based single grade motor oil formulated with specific marine additives. Due to a naturally high viscosity index it provides a stable lubrication film under all operating conditions. Prevents sludge formation and offers good corrosion protection. Particularly suited for use with older engine designs and transmissions.

Specifications and approvals: ACEA E2, API SJ, API CF, API CF-4

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: MAN 270, Volvo VDS

For 4-stroke gasoline engines where a motor oil according to current product specifications is required or recommended, particularly suitable for Mercury Verado engines. Safe with or without catalytic converters and turbochargers. Observe the manufacturers instructions!

4 l	4	22512 ²⁶
205 l	1	22507 ²⁶

MOTOR OILS 2-STROKE



Marine 2T DFI Motor Oil

Semi-synthetic high-performance 2-stroke motor oil developed with state-of-the-art agents specifically for use with late generation, high stress direct fuel injection marine engines. Ensures optimum lubrication and prevents deposit build-up even at high operating temperatures to allow maximum engine life and lowest emission values.

Specifications and approvals: NMMA TC-W3®

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Evinrude E-Tec Engines, ISO L-EGC, ISO L-EGD, JASO FC, JASO FD, Mercury DFI 2 stroke Engines

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For 4-stroke gasoline and diesel engines as well as transmissions where a single-grade fluid according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

1 l	6	22516 ²¹
4 l	4	20518 ²⁶
20 l	1	20494 ²⁶
205 l	1	22515 ²⁶



GEAR OILS



Marine ATF

Fully synthetic ATF fluid specially developed for marine use. Offers increased corrosion protection, high thermal stability and minimizes wear compared with conventional hydraulic fluids. Ensures excellent protective properties and guarantees proper hydraulic function. Compatible with all common sealing materials.

Specifications and approvals: ZF TE-ML 04D, ZF approval number ZF004927

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: Allison C4, Dexron II D, Dexron II E, Dexron III G, Dexron III H, Dexron TASA (Typ A/Suffix A), Mariner, MerCruiser, Mercury

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For drives and transmissions such as reverse gears, steering systems, trim systems, hydrostatic transmission ratios as well as hydraulic and mechanical systems where a fluid meeting current product specifications is required. Observe the manufacturers instructions!

1 l	6	20544 ²⁶
-----	---	---------------------



Marine High Performance Gear Oil SAE 85W-90

Special high-performance gear lube specifically for marine use. Formulated with a unique additive package that guarantees outstanding wear protection even if contaminated with water. Stable under extreme pressure, high stress and at high speeds. Offers outstanding corrosion protection and very good oxidation resistance. Fluid color is blue.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

For transmissions where a high-performance gear lube with current product specifications is required or recommended. Specifically suited for Mercury outboard motors as of 75 hp output as well as MerCruiser Z-drives. Can be used as a replacement for a high-performance gear lube with viscosity SAE 90. Observe the manufacturers instructions!

1 l	6	20536 ²⁶
20 l	1	20492 ²⁶
60 l	1	20493 ²⁶
205 l	1	22524 ²⁶

For specifications and manufacturers' approvals, see the oil guide or technical data sheet. Comply with the vehicle or aggregate manufacturer's instructions.

GEAR OILS



Marine Fully Synthetic Gear Oil GL4/GL5 SAE 75W-90

Fully synthetic high-performance gear oil with extreme performance reserves. Provides accurate transmission function in extreme operating conditions and when exposed to large temperature fluctuations. Meets or exceeds the requirements and specifications of major transmission manufacturers.

Specifications and approvals: API GL4/5, API MT-1

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required: ZF TE-ML 02B, ZF TE-ML 05A, ZF TE-ML 12L, ZF TE-ML 12N, ZF TE-ML 16F, ZF TE-ML 17B, ZF TE-ML 19C, ZF TE-ML 21A

Area of Use

Cont. Packaging Unit Part No.

1 l	6	20538	26
20 l	1	20491	26

For transmissions where a high-performance gear lube with current product specifications is required or recommended. Observe the manufacturers instructions!

ACCESSORIES



Hand Pump

Hand pump supplied with universal hose, metric to U.S. thread adapter for easy filling of outboard engines, transmissions, differentials and other units. Universal use on lawnmowers, ride-on mowers, snow blowers, motorcycle engines and transmissions etc. Fits all LIQUI MOLY 1 Liter containers.

For filling transmissions and other units such as outboard motors, lawnmowers, emergency power units, riding mowers, snow blowers or motorcycle transmissions.

1 Piece	1	29026	26
---------	---	-------	----



Oil Filling Unit for Transmissions

- Tank volume: 7 Liters
- Filling hose: 1,600 mm (5.2' / 63")
- includes 16 adapter for BMW, Ford, Mercedes-Benz, Volkswagen, etc.
- Drip pan

For filling transmissions and differentials with oil. Specifically for dual-clutch transmissions.

1 Piece	1	7941	26
---------	---	------	----

Gun Care Products



GUNTEC Gun Grease

A very cohesive specialty grease with special ceramic lubricants for ultimate performance and safe operation. Ceramic lubricants provide minimal friction and reduce wear for maximum reliability even in critical situations or in extreme temperatures. Safeguards corrosion protection on all metal surfaces.

Used when lubricating handguns, rifles and shotguns and for use on various weapon components. Highly recommended for metal-plastic, plastic-plastic and metal-metal friction pairings such as polymer hand gun slides and rifle bolt actions. Excellent for use on other precision components. Recommended for use in low temperatures and during wide temperature swings.

50 ml	12	24404	26
-------	----	-------	----

WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



GUNTEC Gun Oil

A very cohesive, mid-viscosity specialty oil for lubrication and preservation of guns, gun parts and metal components. Maximized corrosion protection and exceptional wear protection of all moving parts, thanks to superior lubrication properties. Provides superb penetrating properties and is highly resistant to thickening which makes it ideal and usable when lubricating various precision mechanisms. Universal use on polymers and metals as well as treating and protecting wood rifle stocks.

Used for gun lubrication, protection and preservation. Excellent for lubrication, wear and corrosion protection of machinery, tools, metal components, instruments and more. Exceptional protection against corrosion, rust and erosion from long term storage.

100 ml	6	24402	26
--------	---	-------	----


Contact us now and receive our high-performance support
to accelerate your shop's success to new heights.



Futura Rack



20 l Rack



Aluminium Sign



Clock



Various Marketing Flyers



Countertop Display



Various LIQUI MOLY shop banners available



For further info and more POS material, please contact your LIQUI MOLY representative
or call 1-888-MOLYOIL(665-9645)

LIQUI MOLY



RECEIVE **10% OFF**
ENTER CODE "SAVE10"

Newsletter



Teamstore



BUILT FOR THE SHOP, WORN EVERYWHERE!

TAG US IN YOUR PHOTOS!  @LIQUIMOLY.USA.CANADA
LMTEAMSTORE.COM



FOR THE DRIVERS



CREATING BRAND AWARENESS FOR YOUR SUCCESS

LIQUI MOLY - Quality MOTOR OILS & ADDITIVES
Made in Germany since 1957



LIQUI MOLY OFFERS A FULL LINE OF SPEC OILS, ADDITIVES AND SERVICE PRODUCTS - EVERYTHING FROM ONE SOURCE

- The development of modern engines and exhaust after treatment requires specially formulated oils, which are now in higher demand than ever.
- Using the wrong oil can damage your engine and may void the manufacturer's warranty. Always use the recommended oil type to ensure function and maintain warranty coverage.
- Gain a competitive advantage over other distributors or repair shops who do not offer approved oils.
- Using the right oil is key to maintaining your car's performance, which helps extend its life.

MARKETING:

- Strategic Sponsoring (F1, Moto GP, Turner Motorsport, etc.)
- Brand presence at more than 400 events per year
- Shop signage program
- Magazine and digital ads
- Participation in premier racing series such as IMSA, Formula Drift, TC America and more
- POS material for distributors and shops
- LIQUI MOLY's social media effort builds visibility and awareness by sharing engaging stories and product highlights, helping partners connect with customers and grow in the automotive community

OUR SALES FORCE:

- More than 60 local representatives, actively promoting LIQUI MOLY
- Present in all major markets throughout the USA and Canada
- Staff training
- Technical demos
- Workshop branding



TECNICAL



Unitronic, a prominent Canadian company, has established a strong reputation for its specialization in performance software tuning for vehicles. By skillfully optimizing engine control modules (ECMs), Unitronic elevates car performance, amplifying power output and refining driving dynamics. The company mutually supports teams like JDC Miller Motorsports, showcasing its expertise on track at the highest levels of motorsport. Notably, Unitronic has formed a strong partnership with LIQUI MOLY, combining their expertise in software tuning with LIQUI MOLY's high-quality lubricants and additives for a comprehensive automotive enhancement package.



Turner Motorsports, a respected motorsport team with a rich competitive history, has forged a noteworthy partnership with LIQUI MOLY. This collaboration enhances their illustrious reputation by emphasizing joint values of innovation, precision, and cooperative success in the ever-evolving world of motorsport. Actively competing in both IMSA and SRO, Turner Motorsports has built a reputation for consistently securing podium finishes and race wins. Renowned for their exceptional achievements across multiple racing disciplines, the Turner Motorsports and LIQUI MOLY alliance underscores their shared commitment to excellence on and off the track.



Girls Auto Clinic (GAC), a trailblazing automotive service and education organization, is dedicated to empowering women through car care knowledge and professional maintenance services. Established to foster confidence and independence among women drivers, GAC hosts clinics and workshops focused on vehicle education. LIQUI MOLY proudly partners with GAC by contributing expert insights at these events and providing premium lubricants and additives, reinforcing a shared commitment to education, reliability, and excellence in automotive care.

PARTNERS



Off Road Warehouse stands as a premier destination for off-road enthusiasts, offering a wide range of high-quality products and accessories to enhance outdoor adventures. Their collaboration with LIQUI MOLY, has fortified their commitment to excellence by providing customers with top-tier engine oils and performance-enhancing additives, ensuring optimal performance and durability for all off-road vehicles. This partnership reflects a shared dedication to delivering superior products tailored to the unique demands of off-road exploration.



GENRACER

Genracer has established itself as a prominent name in the automotive aftermarket industry, specializing in performance parts and accessories for a range of vehicle makes and models. As a premier source for Hyundai parts, Genracer also competes in TC America, further proving its expertise and commitment to performance on the track. Their partnership with LIQUI MOLY brings together this racing pedigree and aftermarket knowledge to offer enthusiasts a comprehensive solution for enhancing vehicle performance and longevity. This collaboration combines Genracer's product expertise with LIQUI MOLY's top-notch lubrication technology, providing customers with a one-stop shop for optimizing their driving experience.



Beta Motorcycles, an Italian leader in off-road and trials motorcycles, has forged a partnership with LIQUI MOLY. Actively competing in SuperCross and off-road racing, Beta showcases its innovation and competitive spirit on some of the sport's biggest stages. This collaboration brings together Beta's advanced two-wheeler expertise with LIQUI MOLY's engine care excellence, enhancing both the performance and longevity of Beta motorcycles. The partnership reflects a shared commitment to delivering top-tier products that meet the demands of riders and enthusiasts worldwide.

Table of Contents

Part-No.	Description	Cont.	P.U.	Country Available	Page
1564	Motorbike 4T Synth SAE 10W-50 Street Race	60 l	1	USA AND CANADA (-EN-F-)	40
1569	Motorbike 4T Synth SAE 10W-50 Street Race	205 l	1	USA AND CANADA (-EN-F-)	40
2000	Diesel Particulate Filter Protector	250 ml	6	USA (-EN-)	8
2001	Valve Clean	150 ml	12	USA (-EN-)	7
2002	Super Diesel Additive	300 ml	12	USA (-EN-)	8
2003	Long-Life Grease + MoS ₂	100 g	12	USA AND CANADA (-EN-F-)	14
2004	Top Tec 4200 SAE 5W-30 New Generation	1 l	6	USA AND CANADA (-EN-F-)	18
2005	Diesel Purge	500 ml	12	USA (-EN-)	8
2007	Jectron Fuel Injection Cleaner	300 ml	12	USA (-EN-)	7
2009	MoS ₂ Anti-Friction Engine Treatment	300 ml	12	USA AND CANADA (-EN-F-)	6
2011	Top Tec 4200 SAE 5W-30 New Generation	5 l	4	USA AND CANADA (-EN-F-)	18
2012	LM 508 Anti-Seize Compound	100 g	12	USA AND CANADA (-EN-F-)	15
2019	MoS ₂ Antifriction for Gears	50 g	12	USA (-EN-)	7
2020	Motor Oil Saver	300 ml	12	USA (-EN-)	6
2022	Diesel High Tech SAE 5W-40	5 l	4	USA AND CANADA (-EN-F-)	19
2024	Synthoil Race Tech GT1 SAE 10W-60	5 l	4	USA AND CANADA (-EN-F-)	17
2030	Pro-Line Gasoline System Cleaner	500 ml	6	USA (-EN-)	11
2032	Pro-Line Diesel System Cleaner	500 ml	6	USA (-EN-)	11
2037	Pro-Line Engine Flush	500 ml	6	USA (-EN-)	10
2038	Longtime High Tech SAE 5W-30	1 l	6	USA AND CANADA (-EN-F-)	18
2039	Longtime High Tech SAE 5W-30	5 l	4	USA AND CANADA (-EN-F-)	18
2040	Synthoil Premium SAE 5W-40	1 l	12	USA AND CANADA (-EN-F-)	16
2041	Synthoil Premium SAE 5W-40	5 l	4	USA AND CANADA (-EN-F-)	16
2042	MoS ₂ Antifriction SAE 10W-40	1 l	12	USA AND CANADA (-EN-F-)	21
2043	MoS ₂ Antifriction SAE 10W-40	5 l	4	USA AND CANADA (-EN-F-)	21
2044	Touring High Tech Diesel Specialoil SAE 15W-40	5 l	4	USA AND CANADA (-EN-F-)	24;24
2049	Synthoil Energy A40 SAE 0W-40	1 l	6	USA AND CANADA (-EN-F-)	16
2050	Synthoil Energy A40 SAE 0W-40	5 l	4	USA AND CANADA (-EN-F-)	16
2051	Radiator Cleaner	300 ml	12	USA (-EN-)	9
2068	Synthoil Race Tech GT1 SAE 10W-60	1 l	6	USA AND CANADA (-EN-F-)	17
2069	Synthoil Premium SAE 5W-40	205 l	1	USA AND CANADA (-EN-F-)	16
2099	Synthoil Premium SAE 5W-40	60 l	1	USA AND CANADA (-EN-F-)	16
2207	Special Tec AA SAE 0W-20	1 l	6	USA AND CANADA (-EN-F-)	21
2208	Special Tec AA SAE 0W-20	5 l	4	USA AND CANADA (-EN-F-)	21
2248	Special Tec LL SAE 5W-30	1 l	6	USA AND CANADA (-EN-F-)	16
2249	Special Tec LL SAE 5W-30	5 l	4	USA AND CANADA (-EN-F-)	16
2258	Special Tec AA SAE 5W-20	1 l	6	USA AND CANADA (-EN-F-)	22
2259	Special Tec AA SAE 5W-20	5 l	4	USA AND CANADA (-EN-F-)	22
2263	Special Tec F ECO SAE 5W-20	1 l	6	USA AND CANADA (-EN-F-)	20
2264	Special Tec F ECO SAE 5W-20	5 l	4	USA AND CANADA (-EN-F-)	20
2329	Top Tec 4100 SAE 5W-40	1 l	6	USA AND CANADA (-EN-F-)	19
2330	Top Tec 4100 SAE 5W-40	5 l	4	USA AND CANADA (-EN-F-)	19
2331	Leichtlauf High Tech SAE 5W-40	1 l	6	USA AND CANADA (-EN-F-)	16
2332	Leichtlauf High Tech SAE 5W-40	5 l	4	USA AND CANADA (-EN-F-)	16
2593	Motorbike 4T Synth 5W-40 Street Race	60 l	1	USA AND CANADA (-EN-F-)	40
2594	Motorbike 4T Synth 5W-40 Street Race	205 l	1	USA AND CANADA (-EN-F-)	40
2724	Motorbike 4T Synth SAE 10W-60 Street Race	60 l	1	USA AND CANADA (-EN-F-)	41
3316	Pump Spray Bottle	1 l	1	USA AND CANADA (-EN-F-)	35
3323	Drain Cock 3/4" a	1 Piece	1	USA AND CANADA (-EN-F-)	37
3329	3/4" Ball Drain Faucet	1 Piece	1	USA AND CANADA (-EN-F-)	36
3385	Drain Cock in Brass	1 Piece	1	USA AND CANADA (-EN-F-)	37
4090	Air-Conditioner System Cleaner Gun	1 Piece	1	USA AND CANADA (-EN-F-)	13
4099	Air-Conditioning System Gun Probe	1 Piece	1	USA AND CANADA (-EN-F-)	13
7701	Valve Clean	150 ml	12	CANADA (-EN-F-)	7
7702	Super Diesel Additive	300 ml	12	CANADA (-EN-F-)	8
7704	Diesel Purge	500 ml	12	CANADA (-EN-F-)	8
7711	Jectron Fuel Injection Cleaner	300 ml	12	CANADA (-EN-F-)	7
7712	Pro-Line Engine Flush	500 ml	6	CANADA (-EN-F-)	10
7810	Waste Oil Collecting Tank	1 Piece	1	USA AND CANADA (-EN-F-)	35
7812	Oil Drip Pan	1 Piece	1	USA AND CANADA (-EN-F-)	35
7828	Waste Oil Collection and Suction Device	1 Piece	1	USA AND CANADA (-EN-F-)	35
7900	Hand Pump for Drums	1 Piece	1	USA AND CANADA (-EN-F-)	36
7912	Trolleys for Containers/Drums	1 Piece	1	USA AND CANADA (-EN-F-)	35

Part-No.	Description	Cont.	P.U.	Country Available	Page
7924	Drain Cock With Seal for 20L Jugs (PVC-Viton)	1 Piece	1	USA AND CANADA (-EN-F-)	36
7928	Hand Drum Pump	1 Piece	1	USA AND CANADA (-EN-F-)	37
7932	Plastic Hand Pump	1 Piece	1	USA AND CANADA (-EN-F-)	36
7941	Oil Filling Unit for Transmissions	1 Piece	1	USA AND CANADA (-EN-F-)	36;45;49
7945	DPF-Probe With 5 Interchangeable Tips	1 Piece	1	USA AND CANADA (-EN-F-)	12
7946	DPF Pressurized Tank Spray Gun	1 Piece	1	USA AND CANADA (-EN-F-)	12
7952	Drum Packet B1	1 Piece	1	USA AND CANADA (-EN-F-)	35
7953	Drum Packet C	1 Piece	1	USA AND CANADA (-EN-F-)	35
7954	Drum Packet D	1 Piece	1	USA AND CANADA (-EN-F-)	35
7986	Pro-Line Gasoline System Cleaner	500 mL	6	CANADA (-EN-F-)	11
20002	Cera Tec	300 mL	6	USA AND CANADA (-EN-F-)	6
20004	Hydraulic Lifter Additive	300 mL	12	USA (-EN-)	6
20006	Diesel High Tech SAE 5W-40	1 l	6	USA AND CANADA (-EN-F-)	19
20010	Hypoid Gear Oil (GL5) SAE 85W-90	1 l	6	USA AND CANADA (-EN-F-)	27
20012	High Performance Gear Oil (GL4+) SAE 75W-90	1 l	6	USA AND CANADA (-EN-F-)	26
20014	High Performance Gear Oil (GL4+) SAE 75W-90	20 L	1	USA AND CANADA (-EN-F-)	26
20016	Gear Oil (GL4) SAE 85W-90	1 l	6	USA AND CANADA (-EN-F-)	26
20018	Top Tec ATF 1200	1 l	6	USA AND CANADA (-EN-F-)	28
20020	Top Tec ATF 1200	5 L	4	USA AND CANADA (-EN-F-)	28
20022	Top Tec ATF 1200	20 L	1	USA AND CANADA (-EN-F-)	28
20024	Top Tec ATF 1600	1 l	6	USA AND CANADA (-EN-F-)	28
20026	Top Tec ATF 1600	20 L	1	USA AND CANADA (-EN-F-)	28
20028	Top Tec ATF 1900	1 l	6	USA (-EN-)	29
20030	Top Tec ATF 1900	20 L	1	USA AND CANADA (-EN-F-)	29
20032	Top Tec ATF 1800	1 l	6	USA AND CANADA (-EN-F-)	28
20034	Top Tec ATF 1800	20 L	1	USA AND CANADA (-EN-F-)	28
20036	Top Tec ATF 1400	1 l	6	USA AND CANADA (-EN-F-)	28
20038	Central Hydraulic System Oil	1 l	6	USA (-EN-)	30
20040	ATF Additive	250 mL	6	USA AND CANADA (-EN-F-)	7
20042	Fully Synthetic Hypoid Gear Oil (GL5) LS SAE 75W-140	1 l	6	USA (-EN-)	27
20044	Dual Clutch Gear Oil 8100	1 l	6	USA AND CANADA (-EN-F-)	26
20046	Dual Clutch Gear Oil 8100	20 L	1	USA AND CANADA (-EN-F-)	26
20048	Motorbike 4T Bike-Additive	125 mL	6	USA (-EN-)	40
20050	Motorbike Engine Flush	250 mL	6	USA (-EN-)	40
20052	Motorbike Gasoline Stabilizer	250 mL	6	USA (-EN-)	40
20054	Motorbike 4T SAE 10W-40 Street	1 l	6	USA AND CANADA (-EN-F-)	41
20056	Motorbike 4T SAE 10W-40 Street	4 l	4	USA AND CANADA (-EN-F-)	41
20058	Motorbike 4T SAE 15W-50 Street	1 l	6	USA AND CANADA (-EN-F-)	41
20060	Motorbike 4T SAE 15W-50 Street	4 l	4	USA AND CANADA (-EN-F-)	41
20062	Motorbike 4T SAE 20W-50 Street	1 l	6	USA AND CANADA (-EN-F-)	42
20064	Motorbike 4T SAE 20W-50 Street	4 l	4	USA AND CANADA (-EN-F-)	42
20066	Motorbike 4T Synth SAE 10W-50 Street Race	1 l	6	USA AND CANADA (-EN-F-)	40
20068	Motorbike 4T Synth SAE 10W-50 Street Race	4 l	4	USA AND CANADA (-EN-F-)	40
20070	Motorbike 4T Synth SAE 10W-60 Street Race	1 l	6	USA AND CANADA (-EN-F-)	41
20072	Motorbike 4T Synth SAE 10W-60 Street Race	4 l	4	USA AND CANADA (-EN-F-)	41
20074	Motorbike 4T Synth 5W-40 Street Race	1 l	6	USA AND CANADA (-EN-F-)	40
20076	Motorbike 4T Synth 5W-40 Street Race	4 l	4	USA AND CANADA (-EN-F-)	40
20078	Motorbike 4T Synth SAE 10W-50 Offroad Race	1 l	6	USA AND CANADA (-EN-F-)	42
20080	Motorbike 4T Synth SAE 10W-50 Offroad Race	4 l	4	USA AND CANADA (-EN-F-)	42
20082	Motorbike 4T SAE 10W-40 Offroad	1 l	6	USA AND CANADA (-EN-F-)	42
20084	Motorbike 4T SAE 10W-40 Offroad	4 l	4	USA AND CANADA (-EN-F-)	42
20086	Motorbike Gear Oil SAE 75W-90	1 l	6	USA AND CANADA (-EN-F-)	43
20088	Motorbike Gear Oil SAE 75W-140 (GL5)	1 l	6	USA AND CANADA (-EN-F-)	43
20092	Motorbike Fork Oil SAE 10W Medium	1 l	6	USA AND CANADA (-EN-F-)	44
20094	Motorbike Fork Oil SAE 5W Light	1 l	6	USA (-EN-)	44
20096	Motorbike Fork Oil SAE 15W Heavy	1 l	6	USA AND CANADA (-EN-F-)	44
20098	Motorbike Fork Oil SAE 7,5W Medium/Light	1 l	6	USA AND CANADA (-EN-F-)	44
20100	Motorbike HD Synth SAE 20W-50 Street	1 l	6	USA AND CANADA (-EN-F-)	42
20102	Motorbike HD Synth SAE 20W-50 Street	4 l	4	USA AND CANADA (-EN-F-)	42
20108	Motorbike Speed Additive	150 mL	6	USA (-EN-)	40
20110	Pro-Line Diesel Particulate Filter Cleaner	1 l	6	USA (-EN-)	11
20112	Pro-Line Diesel Particulate Filter Purge	500 mL	6	USA AND CANADA (-EN-F-)	11
20114	Touring High Tech SAE 20W-50	5 l	4	USA AND CANADA (-EN-F-)	24

Table of Contents



Part-No.	Description	Cont.	P.U.	Country Available	Page
20116	Dual Clutch Gear Oil 8100	5 l	4	USA AND CANADA (-EN-F-)	26
20118	Top Tec ATF 1100	1 l	6	USA AND CANADA (-EN-F-)	28
20121	Top Tec ATF 1400	20 l	1	USA AND CANADA (-EN-F-)	28
20122	Leichtlauf High Tech SAE 5W-40	20 l	1	USA AND CANADA (-EN-F-)	16
20124	Special Tec LL SAE 5W-30	20 l	1	USA AND CANADA (-EN-F-)	16
20125	Top Tec 4200 SAE 5W-30 New Generation	20 l	1	USA AND CANADA (-EN-F-)	18
20126	Special Tec F ECO SAE 5W-20	20 l	1	USA AND CANADA (-EN-F-)	20
20127	Synthoil Race Tech GT1 SAE 10W-60	20 l	1	USA AND CANADA (-EN-F-)	17
20132	Radiator Stop Leak	250 ml	12	USA (-EN-)	9
20136	Special Tec AA SAE 5W-30	1 l	6	USA AND CANADA (-EN-F-)	22
20138	Special Tec AA SAE 5W-30	5 l	4	USA AND CANADA (-EN-F-)	22
20148	Snowmobile Motoroil SAE 0W-40	1 l	6	USA AND CANADA (-EN-F-)	43
20150	Snowmobile Motoroil SAE 0W-40	4 l	4	USA AND CANADA (-EN-F-)	43
20152	Brake Fluid DOT 4	250 ml	24	USA (-EN-)	15
20154	Brake Fluid DOT 4	500 ml	24	USA (-EN-)	15
20158	Brake Fluid DOT 5.1	250 ml	24	USA (-EN-)	15
20160	Motorbike Visor Cleaner	100 ml	12	USA (-EN-)	44
20162	Motorbike Chain Lube	400 ml	12	CANADA (-EN-F-)	45
20178	Motorbike 2T Synth Offroad Race	1 l	6	USA AND CANADA (-EN-F-)	42
20180	Motorbike 2T Synth Offroad Race	4 l	4	USA AND CANADA (-EN-F-)	42
20186	Motorbike 4T Synth SAE 10W-60 Offroad Race	1 l	6	USA AND CANADA (-EN-F-)	42
20188	Motorbike 4T Synth SAE 10W-60 Offroad Race	4 l	4	USA AND CANADA (-EN-F-)	42
20190	Motorbike 4T SAE 10W-40	1 l	6	USA AND CANADA (-EN-F-)	41
20192	Motorbike 4T SAE 10W-40	4 l	4	USA AND CANADA (-EN-F-)	41
20194	Motorbike 4T SAE 10W-40	20 l	1	USA AND CANADA (-EN-F-)	41
20195	Motorbike 4T Synth SAE 10W-60 Offroad Race	20 l	1	USA AND CANADA (-EN-F-)	42
20198	Special Tec V SAE 0W-20	1 l	6	USA AND CANADA (-EN-F-)	19
20200	Special Tec V SAE 0W-20	5 l	4	USA AND CANADA (-EN-F-)	19
20202	Special Tec V SAE 0W-30	1 l	6	USA AND CANADA (-EN-F-)	19
20204	Special Tec V SAE 0W-30	5 l	4	USA AND CANADA (-EN-F-)	19
20206	Viscoplus for Oil	300 ml	12	USA (-EN-)	6
20208	Pro-Line Diesel Intake System Cleaner	400 ml	6	USA (-EN-)	11
20210	Pro-Line Throttle Valve Cleaner	400 ml	6	USA (-EN-)	11
20212	ATV 4T Motoroil SAE 5W-50	1 l	6	USA AND CANADA (-EN-F-)	43
20214	ATV 4T Motoroil SAE 5W-50	4 l	4	USA AND CANADA (-EN-F-)	43
20216	LM 48 Installation Paste	50 g	12	USA AND CANADA (-EN-F-)	14
20224	Pro-Line Automatic Transmission Cleaner	1 l	6	USA AND CANADA (-EN-F-)	10
20226	Molygen New Generation SAE 5W-30	1 l	6	USA AND CANADA (-EN-F-)	23
20228	Molygen New Generation SAE 5W-30	5 l	4	USA AND CANADA (-EN-F-)	23
20230	Molygen New Generation SAE 5W-40	1 l	6	USA AND CANADA (-EN-F-)	23
20232	Molygen New Generation SAE 5W-40	5 l	4	USA AND CANADA (-EN-F-)	23
20234	Speed Tec Gasoline	250 ml	6	USA (-EN-)	7
20236	Top Tec 6200 SAE 0W-20	1 l	6	USA AND CANADA (-EN-F-)	17
20238	Top Tec 6200 SAE 0W-20	5 l	4	USA AND CANADA (-EN-F-)	17
20240	Brake Anti-Squeal Paste	200 ml	6	USA (-EN-)	14
20242	Ceramic Paste	200 ml	6	USA (-EN-)	14
20244	Battery Clamp Grease	50 g	12	USA (-EN-)	14
20246	Multipurpose Grease	400 g	12	USA AND CANADA (-EN-F-)	14
20248	LM 50 Litho HT	400 g	12	USA AND CANADA (-EN-F-)	14
20250	Truck Series Complete Gasoline System Cleaner	500 ml	6	USA (-EN-)	9
20252	Truck Series Complete Diesel System Cleaner	500 ml	6	USA (-EN-)	9
20254	Truck Series Diesel Performance and Protectant	500 ml	6	USA (-EN-)	9
20256	Truck Series Oil Treatment	500 ml	6	USA AND CANADA (-EN-F-)	9
20258	Truck Series DPF Protector	500 ml	6	USA (-EN-)	9
20262	Classic Motoroil SAE 20W-50 HD	5 l	4	USA AND CANADA (-EN-F-)	24
20284	Power Steering Oil Leak Stop	35 ml	12	USA AND CANADA (-EN-F-)	7
20288	Hybrid Additive	250 ml	6	USA (-EN-)	8
20290	Motorbike Shock Absorber Oil Race	1 l	6	USA AND CANADA (-EN-F-)	44
20292	Motorbike Shock Absorber Oil Race	20 l	1	USA AND CANADA (-EN-F-)	44
20293	Motorbike Shock Absorber Oil	20 l	1	USA AND CANADA (-EN-F-)	44
20294	Motorbike Shock Absorber Oil	1 l	6	USA AND CANADA (-EN-F-)	44
20298	Electronic Spray	200 ml	6	USA (-EN-)	15
20302	Motorbike 4T SAE 10W-40 Street	20 l	1	USA AND CANADA (-EN-F-)	41

Part-No.	Description	Cont.	P.U.	Country Available	Page
20303	Motorbike 4T Synth SAE 10W-60 Street Race	20 l	1	USA AND CANADA (-EN-F-)	41
20304	Motorbike 4T Synth 5W-40 Street Race	20 l	1	USA AND CANADA (-EN-F-)	40
20305	Motorbike 4T Synth SAE 10W-50 Street Race	20 l	1	USA AND CANADA (-EN-F-)	40
20306	Motorbike 4T SAE 10W-40 Offroad	20 l	1	USA AND CANADA (-EN-F-)	42
20307	Motorbike 4T Synth SAE 10W-50 Offroad Race	20 l	1	USA AND CANADA (-EN-F-)	42
20310	Molygen New Generation SAE 5W-50	5 l	4	USA AND CANADA (-EN-F-)	23
20320	Motor Oil Saver	300 mL	12	CANADA (-EN-F-)	6
20322	Pro-Line Diesel Particulate Filter Cleaner	1 l	6	CANADA (-EN-F-)	11
20324	Special Tec AA SAE 0W-16	1 l	6	USA AND CANADA (-EN-F-)	21
20326	Central Hydraulic System Oil	1 l	6	CANADA (-EN-F-)	30
20328	Special Tec AA SAE 0W-16	5 l	4	USA AND CANADA (-EN-F-)	21
20330	Hydraulic Lifter Additive	300 mL	12	CANADA (-EN-F-)	6
20332	Radiator Stop Leak	250 mL	12	CANADA (-EN-F-)	9
20336	Radiator Cleaner	300 mL	12	CANADA (-EN-F-)	9
20338	Viscoplus for Oil	300 mL	12	CANADA (-EN-F-)	6
20340	Speed Tec Gasoline	250 mL	6	CANADA (-EN-F-)	7
20342	Hybrid Additive	250 mL	6	CANADA (-EN-F-)	8
20344	Special Tec AA SAE 10W-30 Diesel	20 l	1	USA AND CANADA (-EN-F-)	22;22;25
20345	Top Tec 4600 SAE 5W-30	20 l	1	USA AND CANADA (-EN-F-)	18
20350	Motorbike Chain Lube	400 mL	12	USA (-EN-)	45
20352	Top Tec MTF 5100 SAE 75W	1 l	6	USA AND CANADA (-EN-F-)	25
20355	Special Tec V SAE 0W-20	60 l	1	USA AND CANADA (-EN-F-)	19
20356	Snowbike Motor Oil SAE 0W-40	1 l	6	USA AND CANADA (-EN-F-)	43
20358	Snowbike Motor Oil SAE 0W-40	4 l	4	USA AND CANADA (-EN-F-)	43
20360	Top Tec ATF 1900	1 l	6	CANADA (-EN-F-)	29
20362	Leichtlauf High Tech SAE 5W-40	60 l	1	USA AND CANADA (-EN-F-)	16
20363	Leichtlauf High Tech SAE 5W-40	205 l	1	USA AND CANADA (-EN-F-)	16
20364	Special Tec LL SAE 5W-30	60 l	1	USA AND CANADA (-EN-F-)	16
20365	Special Tec LL SAE 5W-30	205 l	1	USA AND CANADA (-EN-F-)	16
20366	Special Tec AA SAE 0W-20	60 l	1	USA AND CANADA (-EN-F-)	21
20367	Special Tec AA SAE 0W-20	205 l	1	USA AND CANADA (-EN-F-)	21
20368	Special Tec AA SAE 5W-20	60 l	1	USA AND CANADA (-EN-F-)	22
20369	Special Tec AA SAE 5W-20	205 l	1	USA AND CANADA (-EN-F-)	22
20374	Synthoil Race Tech GT1 SAE 10W-60	60 l	1	USA AND CANADA (-EN-F-)	17
20375	Synthoil Race Tech GT1 SAE 10W-60	205 l	1	USA AND CANADA (-EN-F-)	17
20381	Special Tec AA SAE 5W-30	205 l	1	USA AND CANADA (-EN-F-)	22
20383	Top Tec Truck 4450 SAE 15W-40	20 l	1	USA AND CANADA (-EN-F-)	25
20384	Scratch Stop	200 mL	12	USA AND CANADA (-EN-F-)	38
20388	Windshield Washer Fluid Concentrate Lemon	20 mL	50	USA (-EN-)	38
20392	Car Interior Cleaner	500 mL	6	USA AND CANADA (-EN-F-)	38
20394	Leather Care	250 mL	6	USA (-EN-)	38
20396	Universal Cleaner	1 l	6	USA (-EN-)	38
20398	Pro-Line Diesel System Cleaner	500 mL	6	CANADA (-EN-F-)	11
20402	Motorbike Fork Oil SAE 5W Light	20 l	1	USA AND CANADA (-EN-F-)	44
20403	Motorbike Fork Oil SAE 7,5W Medium/Light	20 l	1	USA AND CANADA (-EN-F-)	44
20404	Motorbike Fork Oil SAE 10W Medium	20 l	1	USA AND CANADA (-EN-F-)	44
20405	Motorbike Fork Oil SAE 15W Heavy	20 l	1	USA AND CANADA (-EN-F-)	44
20408	Special Tec LR SAE 0W-20	1 l	6	USA AND CANADA (-EN-F-)	19
20410	Special Tec LR SAE 0W-20	5 l	4	USA AND CANADA (-EN-F-)	19
20412	Motorbike 4T SAE 5W-40 HC Street	1 l	6	USA AND CANADA (-EN-F-)	41
20414	Motorbike 4T SAE 5W-40 HC Street	4 l	4	USA AND CANADA (-EN-F-)	41
20416	Motorbike 4T SAE 5W-40 HC Street	20 l	1	USA AND CANADA (-EN-F-)	41
20417	Motorbike 4T SAE 10W-30 Street	20 l	1	USA AND CANADA (-EN-F-)	41
20418	Motorbike 4T SAE 10W-30 Street	1 l	6	USA AND CANADA (-EN-F-)	41
20420	Motorbike 4T SAE 10W-30 Street	4 l	4	USA AND CANADA (-EN-F-)	41
20422	Molygen New Generation SAE 5W-40	205 l	1	USA AND CANADA (-EN-F-)	23
20423	Molygen New Generation SAE 5W-30	205 l	1	USA AND CANADA (-EN-F-)	23
20424	Special Tec AA SAE 5W-40 Diesel	20 l	1	USA AND CANADA (-EN-F-)	22;25
20426	Special Tec AA SAE 5W-40 Diesel	5 l	4	USA AND CANADA (-EN-F-)	22;25
20436	Molygen New Generation SAE 0W-20	1 l	6	USA AND CANADA (-EN-F-)	23
20438	Molygen New Generation SAE 0W-20	5 l	4	USA AND CANADA (-EN-F-)	23
20440	Special Tec AA SAE 10W-30 Diesel	5 l	4	USA AND CANADA (-EN-F-)	22;25
20442	Special Tec B FE SAE 5W-30	1 l	6	USA AND CANADA (-EN-F-)	20

Table of Contents

Part-No.	Description	Cont.	P.U.	Country Available	Page
20444	Special Tec B FE SAE 5W-30	5 l	4	USA AND CANADA (-EN-F-)	20
20446	Top Tec 4600 SAE 5W-30	1 l	6	USA AND CANADA (-EN-F-)	18
20448	Top Tec 4600 SAE 5W-30	5 l	4	USA AND CANADA (-EN-F-)	18
20491	Marine Fully Synthetic Gear Oil GL4/GL5 SAE 75W-90	20 l	1	USA AND CANADA (-EN-F-)	49
20492	Marine High Performance Gear Oil SAE 85W-90	20 l	1	USA AND CANADA (-EN-F-)	48
20493	Marine High Performance Gear Oil SAE 85W-90	60 l	1	USA AND CANADA (-EN-F-)	48
20494	Marine 2T DFI Motor Oil	20 l	1	USA AND CANADA (-EN-F-)	48
20495	Marine 4T Motor Oil SAE 10W-30	20 l	1	USA AND CANADA (-EN-F-)	47
20496	Marine 4T Motor Oil SAE 10W-40	20 l	1	USA AND CANADA (-EN-F-)	47
20497	Marine 4T Motor Oil SAE 10W-40	60 l	1	USA AND CANADA (-EN-F-)	47
20498	Marine 4T Motor Oil SAE 10W-40	205 l	1	USA AND CANADA (-EN-F-)	47
20499	Marine 4T Motor Oil SAE 25W-40	20 l	1	USA AND CANADA (-EN-F-)	47
20502	Marine Gasoline Stabilizer	1 l	6	USA (-EN-)	46
20504	Marine Gasoline System Cleaner	500 ml	6	USA (-EN-)	46
20506	Marine 4T Motor Oil SAE 10W-40	1 l	6	USA AND CANADA (-EN-F-)	47
20508	Marine 4T Motor Oil SAE 10W-40	4 l	4	USA AND CANADA (-EN-F-)	47
20518	Marine 2T DFI Motor Oil	4 l	4	USA AND CANADA (-EN-F-)	48
20520	Marine 4T Motor Oil SAE 10W-30	1 l	6	USA AND CANADA (-EN-F-)	47
20522	Marine 4T Motor Oil SAE 10W-30	4 l	4	USA AND CANADA (-EN-F-)	47
20524	Marine Winch Grease	100 g	6	USA AND CANADA (-EN-F-)	47
20526	Marine Super Diesel Additive	500 ml	6	CANADA (-EN-F-)	46
20528	Marine PWC Oil SAE 10W-40	1 l	6	USA AND CANADA (-EN-F-)	47
20530	Marine PWC Oil SAE 10W-40	4 l	4	USA AND CANADA (-EN-F-)	47
20536	Marine High Performance Gear Oil SAE 85W-90	1 l	6	USA AND CANADA (-EN-F-)	48
20538	Marine Fully Synthetic Gear Oil GL4/GL5 SAE 75W-90	1 l	6	USA AND CANADA (-EN-F-)	49
20540	Marine Grease	250 g	12	USA AND CANADA (-EN-F-)	46
20542	Marine Grease	400 g	12	USA AND CANADA (-EN-F-)	46
20544	Marine ATF	1 l	6	USA AND CANADA (-EN-F-)	48
20546	Marine 4T Motor Oil SAE 25W-40	1 l	6	USA AND CANADA (-EN-F-)	47
20548	Marine 4T Motor Oil SAE 25W-40	4 l	4	USA AND CANADA (-EN-F-)	47
20550	Marine Super Diesel Additive	500 ml	6	USA (-EN-)	46
20552	Marine Super Diesel Additive	1 l	6	USA (-EN-)	46
20630	DPF Spray Probe, Long (30 cm)	1 Piece	1	USA AND CANADA (-EN-F-)	12
20731	Leichtlauf High Tech SAE 5W-40	1000 l	1	USA AND CANADA (-EN-F-)	16
20733	Special Tec LL SAE 5W-30	1000 l	1	USA AND CANADA (-EN-F-)	16
20848	Special Tec F SAE 5W-30	1000 l	1	USA AND CANADA (-EN-F-)	20
21928	Oil and Chemical Binder Plus	10 kg	1	USA AND CANADA (-EN-F-)	20
22034	Top Tec ATF 1950	1 l	6	USA AND CANADA (-EN-F-)	29
22036	Top Tec ATF 1800	5 l	4	USA AND CANADA (-EN-F-)	28
22038	Top Tec Truck 4450 SAE 15W-40	5 l	4	USA AND CANADA (-EN-F-)	25
22040	LM 48 Installation Paste	1 kg	4	USA AND CANADA (-EN-F-)	14
22043	Motorbike 4T SAE 5W-40 HC Street	60 l	1	USA AND CANADA (-EN-F-)	41
22044	Top Tec 6600 SAE 0W-20	1 l	6	USA AND CANADA (-EN-F-)	17
22046	Top Tec 6600 SAE 0W-20	5 l	4	USA AND CANADA (-EN-F-)	17
22048	Top Tec 6600 SAE 0W-20	20 l	1	USA AND CANADA (-EN-F-)	17
22049	Top Tec 6600 SAE 0W-20	205 l	1	USA AND CANADA (-EN-F-)	17
22054	Motorbike 4T SAE 10W-40 Street	60 l	1	USA AND CANADA (-EN-F-)	41
22055	Motorbike 4T SAE 10W-40 Street	205 l	1	USA AND CANADA (-EN-F-)	41
22056	Top Tec ATF 1800	205 l	1	USA AND CANADA (-EN-F-)	28
22058	Synthoil Energy A40 SAE 0W-40	205 l	1	USA AND CANADA (-EN-F-)	16
22059	Motorbike 4T SAE 10W-30 Street	60 l	1	USA AND CANADA (-EN-F-)	41
22060	Motorbike 4T SAE 10W-30 Street	205 l	1	USA AND CANADA (-EN-F-)	41
22061	Motorbike 4T SAE 15W-50 Street	60 l	1	USA AND CANADA (-EN-F-)	41
22062	Motorbike 4T SAE 15W-50 Street	205 l	1	USA AND CANADA (-EN-F-)	41
22063	Motorbike 4T SAE 10W-40	60 l	1	USA AND CANADA (-EN-F-)	41
22064	Motorbike 4T SAE 10W-40	205 l	1	USA AND CANADA (-EN-F-)	41
22065	Top Tec ATF 1800	60 l	1	USA AND CANADA (-EN-F-)	28
22067	Top Tec 4100 SAE 5W-40	60 l	1	USA AND CANADA (-EN-F-)	19
22068	Top Tec 4100 SAE 5W-40	205 l	1	USA AND CANADA (-EN-F-)	19
22069	Motorbike 4T SAE 5W-40 HC Street	205 l	1	USA AND CANADA (-EN-F-)	41
22070	MoS ₂ Antifriction Motoroil SAE 20W-50	1 l	6	USA AND CANADA (-EN-F-)	21
22072	MoS ₂ Antifriction Motoroil SAE 20W-50	5 l	4	USA AND CANADA (-EN-F-)	21
22074	Pro-Line Turbocharger Additive	20 g	12	USA (-EN-)	10

Part-No.	Description	Cont.	P.U.	Country Available	Page
22076	DIjectron	300 ml	12	USA (-EN-)	8
22078	Brake Fluid DOT 4	1 l	6	USA (-EN-)	15
22080	High Performance Gear Oil (GL3+) SAE 75W-80	1 l	6	USA AND CANADA (-EN-F-)	26
22082	Hypoid Gear Oil (GL5) SAE 85W-90	20 l	1	USA AND CANADA (-EN-F-)	27
22083	Fully Synthetic Hypoid Gear Oil (GL4/5) SAE 75W-90	20 l	1	USA AND CANADA (-EN-F-)	27
22084	MoS ₂ Antifriction for Gears	50 g	12	CANADA (-EN-F-)	7
22086	Top Tec 4200 SAE 5W-30 New Generation	60 l	1	USA AND CANADA (-EN-F-)	18
22087	Top Tec 4200 SAE 5W-30 New Generation	205 l	1	USA AND CANADA (-EN-F-)	18
22089	Top Tec 6200 SAE 0W-20	205 l	1	USA AND CANADA (-EN-F-)	17
22090	Fully Synthetic Hypoid Gear Oil (GL4/5) SAE 75W-90	1 l	6	USA AND CANADA (-EN-F-)	27
22092	Brake Anti-Squeal Paste	250 g	6	USA (-EN-)	14
22094	Ceramic Paste	250 g	6	USA AND CANADA (-EN-F-)	14
22096	Motorbike 4T Bike-Additive	125 ml	6	CANADA (-EN-F-)	40
22098	Motorbike Engine Flush	250 ml	6	CANADA (-EN-F-)	40
22102	Motorbike Gasoline Stabilizer	250 ml	6	CANADA (-EN-F-)	40
22104	Motorbike Speed Additive	150 ml	6	CANADA (-EN-F-)	40
22108	Motorbike Fork Oil SAE 5W Light	1 l	6	CANADA (-EN-F-)	44
22110	DIjectron	300 ml	12	CANADA (-EN-F-)	8
22113	Special Tec AA SAE 5W-40 Diesel	205 l	1	USA AND CANADA (-EN-F-)	22;25
22115	Special Tec F ECO SAE 5W-20	205 l	1	USA AND CANADA (-EN-F-)	20
22116	Motorbike 4T SAE 20W-50 Street	20 l	1	USA AND CANADA (-EN-F-)	42
22117	Motorbike 4T SAE 20W-50 Street	60 l	1	USA AND CANADA (-EN-F-)	42
22118	Motorbike HD Synth SAE 20W-50 Street	20 l	1	USA AND CANADA (-EN-F-)	42
22119	Motorbike HD Synth SAE 20W-50 Street	60 l	1	USA AND CANADA (-EN-F-)	42
22120	Top Tec 4110 SAE 5W-40	1 l	6	USA AND CANADA (-EN-F-)	19
22122	Top Tec 4110 SAE 5W-40	5 l	4	USA AND CANADA (-EN-F-)	19
22124	Top Tec 4110 SAE 5W-40	20 l	1	USA AND CANADA (-EN-F-)	19
22125	Top Tec 4110 SAE 5W-40	205 l	1	USA AND CANADA (-EN-F-)	19
22126	Longtime High Tech SAE 5W-30	205 l	1	USA AND CANADA (-EN-F-)	18
22127	Touring High Tech SAE 20W-50	205 l	1	USA AND CANADA (-EN-F-)	24
22128	Top Tec Truck 4450 SAE 15W-40	205 l	1	USA AND CANADA (-EN-F-)	25
22129	Snowmobile Motoroil SAE 0W-40	205 l	1	USA AND CANADA (-EN-F-)	43
22130	Molygen New Generation SAE 0W-20	205 l	1	USA AND CANADA (-EN-F-)	23
22131	Special Tec AA SAE 0W-20	1000 l	1	USA AND CANADA (-EN-F-)	21
22134	Special Tec B FE SAE 5W-30	20 l	1	USA AND CANADA (-EN-F-)	20
22135	Special Tec B FE SAE 5W-30	205 l	1	USA AND CANADA (-EN-F-)	20
22136	Special Tec AA SAE 10W-30 Diesel	205 l	1	USA AND CANADA (-EN-F-)	22;22;25
22137	Special Tec AA SAE 10W-30 Diesel	1000 l	1	USA AND CANADA (-EN-F-)	22;25
22138	Molygen New Generation SAE 0W-20	1000 l	1	USA AND CANADA (-EN-F-)	23
22139	Molygen New Generation SAE 5W-40	1000 l	1	USA AND CANADA (-EN-F-)	23
22140	Top Tec 6600 SAE 0W-20	1000 l	1	USA AND CANADA (-EN-F-)	17
22141	Molygen New Generation SAE 5W-20	1000 l	1	USA AND CANADA (-EN-F-)	23
22145	Top Tec ATF 1800 R	20 l	1	USA AND CANADA (-EN-F-)	29
22146	Leichtlauf HC7 SAE 5W-40	205 l	1	USA AND CANADA (-EN-F-)	20
22147	Leichtlauf HC7 SAE 5W-40	1000 l	1	USA AND CANADA (-EN-F-)	20
22148	Longtime High Tech SAE 5W-30	1000 l	1	USA AND CANADA (-EN-F-)	18
22149	Classic Motoroil SAE 20W-50 HD	205 l	1	USA AND CANADA (-EN-F-)	24
22151	Top Tec 4600 SAE 5W-30	205 l	1	USA AND CANADA (-EN-F-)	18
22152	Molygen New Generation SAE 5W-20	5 l	4	USA AND CANADA (-EN-F-)	23
22154	Molygen New Generation SAE 5W-20	205 l	1	USA AND CANADA (-EN-F-)	23
22155	Top Tec 4200 SAE 5W-30 New Generation	1000 l	1	USA AND CANADA (-EN-F-)	18
22156	Top Tec 4210 SAE 0W-30	1 l	6	USA AND CANADA (-EN-F-)	17
22158	Top Tec 4210 SAE 0W-30	5 l	4	USA AND CANADA (-EN-F-)	17
22160	Top Tec 4210 SAE 0W-30	20 l	1	USA AND CANADA (-EN-F-)	17
22161	Top Tec 4210 SAE 0W-30	60 l	1	USA AND CANADA (-EN-F-)	17
22162	Top Tec 4210 SAE 0W-30	205 l	1	USA AND CANADA (-EN-F-)	17
22164	Top Tec 6200 SAE 0W-20	1000 l	1	USA AND CANADA (-EN-F-)	17
22165	Special Tec B FE SAE 5W-30	1000 l	1	USA AND CANADA (-EN-F-)	20
22166	Special Tec AA SAE 5W-20	1000 l	1	USA AND CANADA (-EN-F-)	22
22167	Special Tec AA SAE 5W-30	1000 l	1	USA AND CANADA (-EN-F-)	22
22168	Top Tec 4210 SAE 0W-30	1000 l	1	USA AND CANADA (-EN-F-)	17
22169	Touring High Tech SAE 20W-50	1000 l	1	USA AND CANADA (-EN-F-)	24
22170	Motorbike Visor Cleaner	100 ml	12	CANADA (-EN-F-)	44

Table of Contents



Part-No.	Description	Cont.	P.U.	Country Available	Page
22172	Special Tec V SAE 0W-20	1000 l	1	USA AND CANADA (-EN-F-)	19
22173	Top Tec ATF 1800	1000 l	1	USA AND CANADA (-EN-F-)	28
22174	Top Tec Truck 4450 SAE 15W-40	1000 l	1	USA AND CANADA (-EN-F-)	25
22175	Top Tec 4600 SAE 5W-30	1000 l	1	USA AND CANADA (-EN-F-)	18
22176	Motorbike 4T SAE 20W-50 Street	205 l	1	USA AND CANADA (-EN-F-)	42
22177	Truck Long-life Motor Oil SAE 10W-40	1000 l	1	USA AND CANADA (-EN-F-)	25
22178	Fully Synthetic Hypoid Gear Oil (GL5) LS SAE 75W-140	1 l	6	CANADA (-EN-F-)	27
22180	Top Tec Truck 4350 SAE 5W-30	20 l	1	USA AND CANADA (-EN-F-)	24
22182	Central Hydraulic System Oil 2600	1 l	6	USA AND CANADA (-EN-F-)	30
22184	Top Tec ATF 1800 R	205 l	1	USA AND CANADA (-EN-F-)	29
22185	Top Tec ATF 1800 R	1000 l	1	USA AND CANADA (-EN-F-)	29
22186	Top Tec 6200 SAE 0W-20	20 l	1	USA AND CANADA (-EN-F-)	17
22187	Central Hydraulic System Oil	205 l	1	USA AND CANADA (-EN-F-)	30
22188	Brake & Parts Cleaner	500 ml	12	USA (-EN-)	39
22190	Top Tec 6610 SAE 0W-20	5 l	4	USA AND CANADA (-EN-F-)	17
22193	Top Tec 6610 SAE 0W-20	205 l	1	USA AND CANADA (-EN-F-)	17
22194	Multi-Disc Clutch Oil	1 l	6	USA AND CANADA (-EN-F-)	27
22196	Touring High Tech SAE 10W-30	5 l	4	USA AND CANADA (-EN-F-)	24
22198	Gear Hydraulic Oil TO-4 SAE 10W	20 l	1	USA AND CANADA (-EN-F-)	30
22199	Gear Hydraulic Oil TO-4 SAE 30	20 l	1	USA AND CANADA (-EN-F-)	30
22200	Top Tec ATF 1900	1000 l	1	USA AND CANADA (-EN-F-)	29
22221	Molygen New Generation SAE 5W-30	1000 l	1	USA AND CANADA (-EN-F-)	23
22223	DPF/GPF Cleaner	400 ml	12	USA (-EN-)	12
22224	Dual Clutch Gear Oil 8100	205 l	1	USA AND CANADA (-EN-F-)	26
22226	Screw Retainer Medium Strength	10 g	6	USA AND CANADA (-EN-F-)	39
22228	Screw Retainer High Strength	10 g	6	USA AND CANADA (-EN-F-)	39
22230	Leather Care	250 ml	6	CANADA (-EN-F-)	38
22232	Brake Fluid SL6 DOT 4	250 ml	6	USA (-EN-)	15
22234	Molygen New Generation SAE 5W-40	60 l	1	USA AND CANADA (-EN-F-)	23
22235	Top Tec 6200 SAE 0W-20	60 l	1	USA AND CANADA (-EN-F-)	17
22236	Brake & Parts Cleaner	196 l	1	USA (-EN-)	39
22237	Brake Pin Lube	5 g	50	USA AND CANADA (-EN-F-)	15
22238	Brake Fluid SL6 DOT 4	1 l	6	USA (-EN-)	15
22239	Top Tec 6100 SAE 0W-30	1 l	6	USA AND CANADA (-EN-F-)	18
22240	Top Tec 6100 SAE 0W-30	5 l	4	USA AND CANADA (-EN-F-)	18
22241	Top Tec 4500 SAE 5W-30	1000 l	1	USA AND CANADA (-EN-F-)	18
22242	Pro-Line Injector and Glow Plug Dismantling Aid	400 ml	6	USA (-EN-)	11
22243	Pro-Line Injector and Glow Plug Grease	20 g	12	USA (-EN-)	12
22244	Top Tec Gear EV 510	1 l	6	USA AND CANADA (-EN-F-)	27
22245	Pro-Line Super Diesel Additive K	20 l	1	USA (-EN-)	13
22246	Pro-Line Engine Flush	5 l	3	USA (-EN-)	10
22247	Pro-Line Engine Protection	1 l	6	USA (-EN-)	10
22248	Pro-Line Diesel System Cleaner Concentrate	1 l	6	USA (-EN-)	12
22249	Pro-Line Super Diesel Additive	1 l	6	USA (-EN-)	12
22250	Pro-Line Motor Oil Saver	1 l	6	USA (-EN-)	10
22251	Molygen New Generation SAE 0W-16	1 l	6	USA AND CANADA (-EN-F-)	22
22252	Molygen New Generation SAE 0W-16	5 l	4	USA AND CANADA (-EN-F-)	22
22255	Long-Life Grease + MoS ₂	400 g	12	USA AND CANADA (-EN-F-)	14
22256	Top Tec 4500 SAE 5W-30	205 l	1	USA AND CANADA (-EN-F-)	18
22257	Top Tec ATF 1850	1 l	6	USA (-EN-)	29
22258	Top Tec ATF 1850	20 l	1	USA AND CANADA (-EN-F-)	29
22259	Molygen New Generation SAE 5W-50	205 l	1	USA AND CANADA (-EN-F-)	23
22260	Special Tec B FE SAE 0W-30	1 l	6	USA AND CANADA (-EN-F-)	20
22261	Special Tec B FE SAE 0W-30	5 l	4	USA AND CANADA (-EN-F-)	20
22262	Special Tec B FE SAE 0W-30	205 l	1	USA AND CANADA (-EN-F-)	20
22268	Special Tec B FE SAE 0W-30	1000 l	1	USA AND CANADA (-EN-F-)	20
22269	Special Tec B FE SAE 0W-30	20 l	1	USA AND CANADA (-EN-F-)	20
22272	Special Tec AA SAE 0W-20	20 l	1	USA AND CANADA (-EN-F-)	21
22273	Top Tec 4110 SAE 5W-40	1000 l	1	USA AND CANADA (-EN-F-)	19
22274	Top Tec MTF 5300 SAE 70W-75W	1 l	6	USA AND CANADA (-EN-F-)	26
22275	Top Tec MTF 5400 SAE 75W-90	1 l	6	USA AND CANADA (-EN-F-)	26
22276	Leichtlauf High Tech SAE 5W-40	1 l	1	USA AND CANADA (-EN-F-)	16
22278	Special Tec AA SAE 0W-16	205 l	1	USA AND CANADA (-EN-F-)	21

Part-No.	Description	Cont.	P.U.	Country Available	Page
22279	Special Tec AA SAE 0W-8	1 l	6	USA AND CANADA (-EN-F-)	21
22280	Special Tec AA SAE 0W-8	5 l	4	USA AND CANADA (-EN-F-)	21
22281	Special Tec AA SAE 0W-8	20 l	1	USA AND CANADA (-EN-F-)	21
22285	Top Tec ATF 1820	1 l	6	USA AND CANADA (-EN-F-)	29
22286	Brake Fluid DOT 5.1	500 mL	24	USA (-EN-)	15
22287	Brake Fluid DOT 5.1	1 l	6	USA (-EN-)	15
22288	Brake Fluid SL6 DOT 4	500 mL	24	USA (-EN-)	15
22289	Special Tec AA SAE 0W-8	1000 l	1	USA AND CANADA (-EN-F-)	21
22290	Special Tec F SAE 0W-30	1000 l	1	USA AND CANADA (-EN-F-)	20
22291	Top Tec ATF 1950	20 l	1	USA AND CANADA (-EN-F-)	29
22292	Special Tec AA SAE 5W-20	20 l	1	USA AND CANADA (-EN-F-)	22
22293	Special Tec AA SAE 5W-30	20 l	1	USA AND CANADA (-EN-F-)	22
22294	A/C System Cleaner	1 l	6	USA AND CANADA (-EN-F-)	13
22295	Brake Fluid 4 in 1	5 l	4	USA (-EN-)	16
22296	Top Tec ATF 1950	205 l	1	USA AND CANADA (-EN-F-)	29
22299	ATV 4T Motoroil SAE 5W-50	20 l	1	USA AND CANADA (-EN-F-)	43
22300	Motorbike 4T SAE 15W-50 Street	20 l	1	USA AND CANADA (-EN-F-)	41
22301	Special Tec AA SAE 0W-16	20 l	1	USA AND CANADA (-EN-F-)	21
22302	Pro-Line ATF Additiv	250 mL	6	USA AND CANADA (-EN-F-)	10
22507	Marine Single Grade SAE 30	205 l	1	USA AND CANADA (-EN-F-)	48
22508	Marine 4T Motor Oil SAE 25W-50	1 l	6	USA AND CANADA (-EN-F-)	48
22510	Marine 4T Motor Oil SAE 25W-50	4 l	4	USA AND CANADA (-EN-F-)	48
22512	Marine Single Grade SAE 30	4 l	4	USA AND CANADA (-EN-F-)	48
22514	Marine 4T Motor Oil SAE 25W-50	205 l	1	USA AND CANADA (-EN-F-)	48
22515	Marine 2T DFI Motor Oil	205 l	1	USA AND CANADA (-EN-F-)	48
22516	Marine 2T DFI Motor Oil	1 l	6	USA (-EN-)	48
22518	Marine PWC Oil SAE 10W-40	60 l	1	USA AND CANADA (-EN-F-)	47
22519	Marine PWC Oil SAE 10W-40	205 l	1	USA AND CANADA (-EN-F-)	47
22520	Marine 4T Motor Oil SAE 15W-40 New Generation	4 l	4	USA AND CANADA (-EN-F-)	47
22522	Marine 4T Motor Oil SAE 15W-40 New Generation	20 l	1	USA AND CANADA (-EN-F-)	47
22523	Marine 4T Motor Oil SAE 15W-40 New Generation	205 l	1	USA AND CANADA (-EN-F-)	47
22524	Marine High Performance Gear Oil SAE 85W-90	205 l	1	USA AND CANADA (-EN-F-)	48
22525	Marine PWC Oil SAE 10W-40	20 l	1	USA AND CANADA (-EN-F-)	47
24402	GUNTEC Gun Oil	100 mL	6	USA AND CANADA (-EN-F-)	49
24404	GUNTEC Gun Grease	50 mL	12	USA AND CANADA (-EN-F-)	49
25025	Marine 4T Motor Oil SAE 10W-30	60 l	1	USA AND CANADA (-EN-F-)	47
25029	Marine 4T Motor Oil SAE 25W-40	60 l	1	USA AND CANADA (-EN-F-)	47
25057	Marine 4T Motor Oil SAE 25W-40	205 l	1	USA AND CANADA (-EN-F-)	47
25074	Marine 4T Motor Oil SAE 10W-30	205 l	1	USA AND CANADA (-EN-F-)	47
25100	Marine Gasoline Stabilizer Shooter	200 mL	20	USA (-EN-)	46
25102	Marine 4T Shooter	200 mL	20	USA (-EN-)	46
29026	Hand Pump	1 Piece	1	USA AND CANADA (-EN-F-)	36;45;49
29077	Tornador Gun	1 Piece	1	USA AND CANADA (-EN-F-)	38
29130	Sealing Rings (4 Pieces)	1 Piece	1	USA AND CANADA (-EN-F-)	36
29350	Brake Fluid xTronic	1 Piece	1	USA (-EN-)	36
29540	Protective Caps for Drain Cocks (4 Pieces)	1 Piece	1	USA AND CANADA (-EN-F-)	37



LIQUI MOLY USA, INC.
E-mail: info@liqui-moly.com
www.liqui-moly.com

For further information or
technical support please
call 1-888-MOLYOIL (665-9645)
support.north-america@liqui-moly.com

No liability for misprints.
Subject to technical modifications.

 facebook.com/liquimolyus
facebook.com/liquimolyca

 instagram.com/liquimoly.usa.canada

Find the right oil:



Newsletter:



Teamstore:



55892509

